

XCAT 2.x MySQL Setup

Version: 1.0

Date: 01/22/2009

1.0 Switch to the MySQL database on the Management Node.....	1
1.1.1 Install MySQL.....	1
1.1.2 Configure MySQL.....	2
1.1.3 Migrate xCAT data to MySQL.....	5

1.0 Switch to the MySQL database on the Management Node

The xCAT support for Service Nodes requires a database with remote access capabilities. The MySQL database is provided for this purpose. You must be running the xCAT 2.1* code to use MySQL.

1.1.1 Install MySQL

On AIX:

The xCAT RPM called `xcat-mysql-5.1-1` is provided as a convenience to help simplify the installation of MySQL on an AIX system. This RPM includes version 5.1.26 of MySQL, (`mysql-5.1.26-rc-aix5.3-powerpc.tar.gz`) which is available from <http://dev.mysql.com/downloads/mysql/5.1.html#aix>.

You will also need to install `perl-DBD-mysql`.

Both of these packages are included in the `xcat-deps.tar.gz` file that was downloaded when setting up the xCAT management node.

To install the packages use the following commands:

```
rpm -i xcat-mysql-5.1-1.aix5.3.ppc.rpm  
rpm -i perl-DBD-mysql-4.007-1.aix5.3.ppc.rpm
```

The `xcat-mysql` post processing will automatically unwrap MySQL in the `/usr/local` directory and will create a link for `/usr/local/mysql`. I will also update the `PATH` environment variable in the `/etc/profile` file.

On Linux:

MySQL comes as part of the OS. Insure that the following rpms are installed on your Management Node:

perl-DBD-MySQL*

mysql-server-5.*

mysql-5.*

mysql-devel-5.*

mysql-bench-5.*

mysql-5.*

mysql-connector-odbc-*

mysql-devel-5.*

1.1.2 Configure MySQL

To set up the MySQL database on the Management Node follow these steps. (See <http://dev.mysql.com/doc/refman/5.1/en/installing-binary.html> for additional details.)

This example assumes:

- mn20: hostname of management node
- xcatdb: database name
- mysql: database role (aka user)
- xcatadmin database user id used by xCAT for access
- xcat201: database password for xcatadmin

Substitute your addresses and desired database administration, password and database name as appropriate.

On AIX: The example assumes that **mysql** it was installed in */usr/local* and *commands and the database is under /usr/local/mysql* directory.

On Linux: mysql is already installed in /usr/bin and the database is in /var/lib/mysql (tested on Redhat).

Set your paths accordingly.

1. For AIX, add a login user and group for **mysqld** (this is probably already there on Linux):

add the group mysql

add the user mysql

2. On AIX, Update permissions on installed mysql

cd /usr/local/mysql

chown -R mysql .

chgrp -R mysql .

3. Create the MySQL data directory and initialize the grant tables:
On AIX: /usr/local/mysql/scripts/mysql_install_db --user=mysql
On Linux: /usr/bin/mysql_install_db --user=mysql

4. Edit Server config file to run in ASCII-QUOTES mode (required)
On AIX:

```
cp /usr/local/mysql/support-files/my-large.cnf /etc/my.cnf
```

On Linux and AIX: edit /etc/my.cnf .

under the # The MySQL server [mysqld] section

add the following line: *sql_mode = ANSI_QUOTES*

5. On AIX:Update permissions for root to own database

```
cd /usr/local/mysql  
chown -R root .  
chown -R mysql data
```

6. Start the MySQL server (running as root must use the --user option):

On AIX:

```
/usr/local/mysql/bin/mysqld_safe --user=mysql &
```

On Linux:

```
/usr/bin/mysqld_safe --user=mysql &
```

Note: if you get errors such as :

```
/usr/local/mysql/bin/mysqld: Out of memory (Needed 219486208 bytes)
```

```
/usr/local/mysql/bin/mysqld: Out of memory (Needed 164613120 bytes)
```

```
/usr/local/mysql/bin/mysqld: Out of memory (Needed 123457536 bytes)
```

```
/usr/local/mysql/bin/mysqld: Out of memory (Needed 92593152 bytes)
```

Run the command ulimit -a and check the setting for memory:

```
ulimit -a
```

```
time(seconds) unlimited
```

```
file(blocks) 2097151
```

```
data(kbytes) 131072
```

```
stack(kbytes) 32768
```

```
memory(kbytes) 32768
```

```
coredump(blocks) 2097151
```

```
nofiles(descriptors) 2000
```

```
threads(per process) unlimited
```

Change the ulimit memory setting to unlimited.

7. Set the root passwd for the server

ON AIX:
/usr/local/mysql/bin/mysqladmin -u root password
'new-password'
On Linux:
/usr/bin/mysqladmin -u root password 'new-password'

8. If command fails,

On AIX: check the /usr/local/mysql/data/mn20.err
file.

On Linux: check /var/log/mysqld.log

9. To stop MySQL server run the following command:

On AIX: /usr/local/mysql/bin/mysqladmin -u root -p
shutdown

On Linux: /usr/bin/mysqladmin -u root -p shutdown

10. Create the *xcatdb* database.

On AIX: /usr/local/mysql/bin/mysql -u root -p

On Linux: /usr/bin/mysql -u root -p

Enter password:

mysql > CREATE DATABASE xcatdb;

11. Create the xcat admin id with password xcat201 and set permissions.

On AIX: /usr/local/mysql/bin/mysql -u root -p

On Linux: /usr/bin/mysql -u root -p

Enter password:

mysql > CREATE USER xcatadmin IDENTIFIED BY 'xcat201';

mysql > GRANT ALL on xcatdb. TO 'xcatadmin'@'mn20'
IDENTIFIED BY 'xcat201';*

mysql > GRANT ALL on xcatdb. to xcatadmin'@'<servicenode
ip(s)>' IDENTIFIED BY 'xcat201';*

Substitute your own admin id name and password and management node and service node ip address or name.

12. Check the user table.

```
mysql > SELECT host, user FROM mysql.user;
```

13. Check the defined databases.

```
mysql > SHOW DATABASES;
```

14. To run commands against the *xcatdb* database you can enter MySQL commands as follows:

```
mysql > use xcatdb;
```

```
mysql > SHOW TABLES;
```

```
mysql > DESCRIBE <table name>;
```

To exit:

```
mysql > quit;
```

1.1.3 Migrate xCAT data to MySQL

1. Back up your xCAT data. (This is required even if you have not added anything to your xCAT database yet. Required default entries were created when the xCAT RPMs were installed on the management node and they must be migrated to the new MySQL database.)

```
mkdir -p ~/xcat-dbback
```

```
dumpxCATdb -p ~/xcat-dbback
```

2. */etc/xcat/cfgloc* should contain the following line, substituting your specific info. This points the xCAT database access code to the new database.

```
mysql:dbname=xcatdb;host=mn20|xcatadmin|xcat201
```

Note: may need to use long hostname or ip address

```
mysql:dbname=xcatdb;host=mn20.cluster.net|xcatadmin|xcat201
```

3. Copy */etc/xcat/cfgloc* to */install/postscripts/etc/xcat/cfgloc* for installation on the service nodes.

```
mkdir -p /install/postscripts/etc/xcat
```

```
cp /etc/xcat/cfgloc /install/postscripts/etc/xcat/cfgloc
```

```
chmod 700 /etc/xcat/cfgloc
```

4. Restore your database to MySQL (bypass mode runs the command without *xcatd*):

```
XCATBYPASS=1 restorexCATdb -p ~/xcat-dbback
```

5. Start the *xcatd* daemon using the MySQL database

```
service xcatd restart
```

