

xCAT 2.0 on AIX

How-To: Deploy AIX diskless nodes

Version: 1.0

Date: 5/29/2008

| | |
|---------------------------------------------------------------------------------------|--------------------|
| 1.0 Deploying AIX diskless nodes using xCAT..... | 2 |
| 1.1 Assumptions..... | 2 |
| 1.2 Configure NIM | 2 |
| 1.3 Create a diskless image..... | 3 |
| 1.4 Update the SPOT (optional)..... | 4 |
| 1.5 Define xCAT networks..... | 4 |
| 1.6 Define the HMC as an xCAT node..... | 4 |
| 1.7 Discover the LPARs managed by the HMC..... | 5 |
| 1.8 Define xCAT cluster nodes..... | 5 |
| 1.9 Define xCAT groups (optional)..... | 5 |
| 1.10 Set up post boot scripts (optional)..... | 6 |
| 1.11 Initialize the AIX/NIM diskless nodes..... | 6 |
| 1.12 Initiate a network boot..... | 7 |
| 1.13 Verify the deployment..... | 7 |
| 2.0 Updating a NIM SPOT resource..... | 8 |
| 2.1 Install additional software..... | 8 |
| 2.2 Add or modify files..... | 9 |
| 2.3 Use chroot to run commands in the SPOT root directory..... | 10 |
| 3.0 Special Cases..... | 10 |
| 3.1 Using other NIM resources..... | 10 |
| 3.2 Booting a “dataless” node..... | 10 |
| 3.3 Specifying additional values for the NIM node initialization..... | 11 |
| 4.0 Updating AIX diskless nodes using xCAT..... | 11 |
| 4.1 Create a new image..... | 12 |
| 4.1.1 Create a new image from different source..... | 12 |
| 4.1.2 Copy an existing image..... | 12 |
| 4.2 Update the SPOT(COSI) (optional)..... | 13 |
| 4.3 Verify the new image (optional)..... | 13 |
| 4.4 Set up post boot scripts (optional)..... | 13 |
| 4.5 Initialize the NIM diskless nodes..... | 13 |
| 4.6 Verify node readiness (optional)..... | 15 |
| 4.7 Initiate a network boot..... | 15 |
| 4.8 Verify the deployment..... | 15 |
| 5.0 Cleanup..... | 17 |
| 5.1 Removing NIM machine definitions..... | 17 |
| 5.2 Removing NIM resources | 18 |
| 6.0 Notes..... | 18 |
| 6.1 Terminology..... | 18 |
| 6.2 NIM diskless resources..... | 19 |

| | |
|-------------------------------------------------|--------------------|
| 6.3 NIM Commands..... | 20 |
| 6.3.1 COSI commands..... | 20 |
| 6.3.2 Thin server commands..... | 21 |

1.0 Deploying AIX diskless nodes using xCAT

This “How-To” describes how AIX diskless node can be deployed and updated using xCAT and AIX/NIM commands.

NIM is an AIX tool that enables a cluster administrator to centrally manage the installation and configuration of AIX and optional software on machines within a networked environment. Setting up NIM involves various tasks including, installing NIM software, configuring NIM and creating some basic NIM installation resources.

The specific tasks that you need to perform depend on which features of NIM that you plan to use. For more information about NIM, see the *IBM AIX Installation Guide and Reference*. (<http://www-03.ibm.com/servers/aix/library/index.html>)

This “How-To” describes only one basic set of steps that may be used to deploy diskless nodes and is not meant to be comprehensive.

1.1 Assumptions

- An AIX system has been installed to use as an xCAT management node.
- All relevant base AIX services are configured and running. This includes (but is not limited to) bootp, tftp, NFS, and hostname resolution.
- xCAT and prerequisite software has been installed on the management node.
- LPARs have already been created using the HMC interfaces.
- You have some experience using AIX Network Installation Management (NIM).

1.2 Configure NIM

To install the required NIM software and do the NIM configuration you can use the AIX **nim_master_setup** command. This command will install the NIM master file set and do some basic NIM configuration. It can also be used to create some basic NIM resources that can be used to do a standard installation of the nodes. However, in our case we won't be needing those resources so we will run the command as follows:

```
nim_master_setup -a mk_resource=no
```

This assumes that the required NIM software is available on /dev/cd0. If this is not the case then you must specify a different source directory. (ex. -a device=/mnt/610_lpp”)

You could also do the NIM configuration using the AIX SMIT interfaces. (Just type the SMIT fastpath “smit eznim” to get started.)

Note: If you have already configured the NIM master on your xCAT management node you can skip this step.

1.3 Create a diskless image

We need to create an xCAT *osimage* definition as well as the corresponding AIX/NIM resources that will be needed to boot the diskless nodes.

The xCAT *osimage* definition contains the names of the NIM resources as well as other information about how the node should be deployed.

There are several NIM resources that must be created in order to deploy a diskless node. The main resource is the AIX diskless image. Creating an AIX diskless image is actually equivalent to creating a NIM SPOT (Shared Product Object Tree) resource. A SPOT provides a */usr* file system for diskless nodes, a root directory whose contents will be used for the initial diskless node root directory, as well as network boot support. The SPOT resource is also referred to as a Common Operating System Image (COSI).

To do all this you can use the xCAT **mknimimage** command. This command automatically creates the required NIM resources and the associated xCAT *osimage* definition.

See the **mknimimage man** page for additional details.

When you run the command you must provide a source for the installable images. This is typically the AIX product media or the name of a NIM *lpp_source* resource. You must also provide a name for the image you wish to create. This name will be used for the NIM SPOT resource as well as the name of the xCAT *osimage* definition.

For example, to create a diskless image called “*61cosi*” using the AIX product CDs you could issue the following command.

```
mknimimage -t diskless -s /dev/cd0 61cosi
```

(Note that this operation could take a while to complete!)

The command will display a summary of what was created when it completes.

The NIM resources will be created in a subdirectory of */install/nim* by default. You can use the “-l” option to specify a different location.

To display the xCAT image definition run the xCAT **lsdef** command.

```
lsdef -t osimage -l -o 61cosi
```

To get details for the NIM resource definitions use the AIX **lsnim** command. For example, if the name of your SPOT resource is “*61cosi*” then you could get the details by running:

```
lsnim -l 61cosi
```

To see the actual contents of a NIM resource use "*nim -o showres <resource name>*". For example, to get a list of the software installed in your SPOT you could run:

```
nim -o showres 6lcosi
```

1.4 Update the SPOT (optional)

The SPOT (or COSI) created in the previous step should be considered the basic minimal diskless AIX operating system image. It does not contain all the software that would normally be installed as part of AIX if you were installing a standalone system from the AIX product media. (The “*nim -o showres ...*” command mentioned above will display what software is contained in the SPOT.)

You must install any additional software you need and make any customizations to the image before you boot the nodes.

See the section “Updating a NIM SPOT resource” later in this document for details on how to update a SPOT resource.

1.5 Define xCAT networks

Create a network definition for each network that contains cluster nodes. You will need a name for the network and values for the following attributes.

| | |
|----------------|----------------------|
| net | The network address. |
| mask | The network mask. |
| gateway | The network gateway. |

In our example we will assume that all the cluster node management interfaces and the xCAT management node interface are on the same network. You can use the xCAT **mkdef** command to define the network.

For example:

```
mkdef -t network -o net1 net=9.114.113.224 mask=255.255.255.224  
gateway=9.114.113.254
```

Note: NIM also requires network definitions. When NIM was configured in an earlier step the default NIM master network definition was created. The NIM definition should match the one you create for xCAT. If multiple cluster subnets are needed then you will need an xCAT and NIM network definition for each one. A future xCAT enhancement will simplify this by automatically creating NIM network definitions based on the xCAT definitions.

1.6 Define the HMC as an xCAT node

The xCAT hardware control support requires that the hardware control point for the nodes also be defined as a cluster node.

The following command will create an xCAT node definition for an HMC with a host name of “*hmc01*”. The *groups*, *nodetype*, *mgt*, *username*, and *password* attributes must be set.

```
mkdef -t node -o hmc01 groups="all" nodetype=hmc mgt=hmc
username=hscroot password=abc123
```

1.7 Discover the LPARs managed by the HMC

This step assumes that the LPARs were already created using the standard HMC interfaces.

Use the xCAT **rscan** command to gather the LPAR information. In this example we will use the “-z” option to create a stanza file that contains the information gathered by **rscan** as well as some default values that could be used for the node definitions.

To write the stanza format output of **rscan** to a file called “*mystanzafile*” run the following command.

```
rscan -z hmc01 > mystanzafile
```

This file can then be checked and modified as needed. For example you may need to add a different name for the node definition or add additional attributes and values etc.

Note: The stanza file will contain stanzas for objects other than the LPARs. This information must also be defined in the xCAT database. It is not necessary to modify the non-LPAR stanzas in any way.

1.8 Define xCAT cluster nodes

The information gathered by the **rscan** command can be used to create xCAT node definitions.

Since we have put all the node information in a stanza file we can now pass the contents of the file to the **mkdef** command to add the definitions to the database.

```
cat mystanzafile | mkdef -z
```

You can use the xCAT **lsdef** command to check the definitions (ex. “*lsdef -l node01*”). After the node has been defined you can use the **chdef** command to make any additional updates to the definitions, if needed.

1.9 Define xCAT groups (optional)

There are two basic ways to create xCAT node groups. You can either set the “groups” attribute of the node definition or you can create a group directly.

You can set the “groups” attribute of the node definition when you are defining the node with the **mkdef** command or you can modify the attribute later using the **chdef**

command. For example, if you want a set of nodes to be added to the group “aixnodes” you could run **chdef** as follows.

```
chdef -t node -o node01,node02,node03 groups=aixnodes
```

Note that this example will overwrite any value that is currently set. The **chdef** command also has an option for adding to or deleting from an existing attribute value.

The second option would be to create a new group definition directly using the **mkdef** command as follows.

```
mkdef -t group -o aixnodes members="node01,node02,node03"
```

These two options will result in exactly the same definitions and attribute values being created.

1.10 Set up post boot scripts (optional)

- TBD
- add list to “postscripts” node attribute
- copy post scripts to /install/postscripts directories

1.11 Initialize the AIX/NIM diskless nodes

You can set up NIM to support a diskless boot of nodes by using the xCAT **mkdsklsnode** command. This command uses information from the xCAT database and default values to run the appropriate NIM commands.

For example, to set up all the nodes in the group “aixnodes” to boot using the SPOT (COSI) named “61cosi” you could issue the following command.

```
mkdsklsnode -i 61cosi aixnodes
```

The command will define and initialize the NIM machines. It will also set the “profile” attribute in the xCAT node definitions to “61cosi “.

To verify that NIM has allocated the required resources for a node and that the node is ready for a network boot you can run the “**lsnim -l**” command. For example, to check node “node01” you could run the following command.

```
lsnim -l node01
```

Note:

In preparation for the network boot, NIM configures **bootp**. Once the **mkdsklsnode** command completes you can verify that the */etc/bootptab* file has an entry for each node you wish to boot. Also, it is recommended that you stop and restart the **inetd** service to ensure the new **bootp** configuration is loaded:

```
stopsrc -s inetd
```

```
startsrc -s inetd
```

1.12 Initiate a network boot

Initiate a remote network boot request using the xCAT **rnetboot** command. For example, to initiate a network boot of all nodes in the group “aixnodes” you could issue the following command.

```
rnetboot aixnodes
```

Note: If you receive timeout errors from the **rnetboot** command, you may need to increase the default 60-second timeout to a larger value by setting `ppctimeout` in the site table:

```
chdef -t site -o clustersite ppctimeout=180
```

1.13 Verify the deployment

- As soon as the **rnetboot** command returns you can open a remote console to monitor the boot progress using the xCAT **rcons** command. This command requires that you have `conserver` installed and configured. To configure `conserver`, run:

```
makeconservercf
```

Kill the `conserver` daemon if it is running, and restart it:

```
conserver &
```

(You may need to add `/opt/freeware/bin` and `/opt/freeware/sbin` to your `PATH` first).

To start a console:

```
rcons node01
```

- You can use the AIX **lsnim** command to see the state of the NIM installation for a particular node, by running the following command on the NIM master:

```
lsnim -l <clientname>
```

- Retry and troubleshooting tips:
 - For p6 lpar, it may be helpful to bring up the HMC web interface in a browser and watch the lpar status and reference codes as the node boots.
 - Verify network connections
 - If the **rnetboot** returns “unsuccessful” for a node, verify that `bootp` and `tftp` is configured and running properly.
 - View `/etc/bootptab` to make sure an entry exists for the node.
 - Verify that the information in `/tftpboot/<node>.info` is correct.
 - Stop and restart `inetd`:

```
stopsrc -s inetd  
startsrc -s inetd
```

- Stop and restart tftp:
 - stopsrc -s tftp*
 - startsrc -s tftp*
-
- Verify NFS is running properly and mounts can be performed with this NFS server:
 - View */etc/exports* for correct mount information.
 - Run the *showmount* and *exportfs* commands.
 - Stop and restart the NFS and related daemons:
 - stopsrc -g nfs*
 - startsrc -g nfs*
 - Attempt to mount a filesystem from another system on the network.
- If the **rnetboot** operation is successful, but *lsnim* shows that the node is stuck at one of the netboot phases, you may need to redo your NIM definitions. Try the “short” approach first:

```
nim -F -o reset node01
```

```
nim -o dkls_init node01
```

```
rnetboot -f node01
```

- If that doesn't work, you may need to delete the entire client definition from NIM and recreate it:

```
nim -F -o reset node01
```

```
nim -o deallocate -a root=root -a paging=paging -a dump=dump -a spot=61cosi node01
```

```
nim -o remove node01
```

```
mkdsklsnode -i 61cosi node01
```

```
rnetboot -f node01
```

2.0 Updating a NIM SPOT resource

There are three basic processes you can use to update a SPOT (COSI):

1. Install additional **installp** file sets or **rpm** packages.
2. Add or modify specific files, (such as */etc/inittab*).
3. Use the **chroot** command to run commands in the root file system contained in the SPOT.

2.1 Install additional software

You may need to install additional software into the SPOT(COSI) before it is used to boot the nodes.

You can use the AIX **chcosi** command to install both **installp** file sets and **rpm** packages in a SPOT(COSI) resource.

Before running the **chcosi** command you must add the new filesets and/or RPMs to the *lpp_source* resource used to create the COSI. In this case the the *lpp_source* for *61cosi* is */install/nim/lpp_source/61cosi_lpp*. The **installp** packages would go in: */install/nim/lpp_source/61cosi_lpp/installp/ppc* and the RPM packages would go in: */install/nim/lpp_source/61cosi_lpp/RPMS/ppc*.

The **chcosi** command supports installing, updating, rejecting, removing, and committing the **installp** packages in the common image. See the **chcosi** man page details.

For example, to install and commit the optional OpenSSH packages from the AIX Expansion Pack you could issue the following command.

```
chcosi -i -c -s 61cosi_lpp -f openssl.base openssl.license openssl.man.en_US  
openssl.msg.en_US openssl.msg.EN_US 61cosi
```

Any additional software that is needed can be installed in a similar manner.

Note: When installing software into a SPOT the pre and post install scripts for a particular software package will not run any code that will impact your running system, (like restarting daemons etc.). The script will check to see if it's installing into a SPOT and it will not run that code.

RPM packages may also be installed in the diskless image. You can use the **chcosi** command to install an RPM as follows.

```
chcosi -i -s 61cosi_lpp -f R:mypack..aix5.3.ppc.rpm 61cosi
```

2.2 Add or modify files

You can also update files in the SPOT/COSI manually. The root file system for the diskless node will be created by copying the “*inst_root*” directory contained in the SPOT. In the SPOT we created for this example the “*inst_root*” directory would be:

```
/install/nim/spot/61cosi/usr/lpp/bos/inst_root/
```

For example, if you need to update the */etc/inittab* file that will be used on the diskless nodes you could edit:

```
/install/nim/spot/61cosi/usr/lpp/bos/inst_root/etc/inittab
```

You can also copy specific files into the *inst_root* directory so they will be available when the nodes boot. For example, you could copy a script called *myscript* to */install/nim/spot/61cosi/usr/lpp/bos/inst_root/opt/foo/myscript* and then add an entry to */etc/inittab* so that it would be run when the node boots.

All the diskless nodes that are booted using this SPOT will get a copy of *inst_root* as the initial root directory.

There are several files that you may want to consider updating in the SPOT *inst_root* directory. For example:

- */etc/hosts*
- */etc/resolv.conf*
- */etc/password*

- /etc/profile
- etc.

2.3 Use chroot to run commands in the SPOT root directory

TBD!!!!

- use chroot to run cmds in new root env – include mount of /usr??

Notes – need to add explanation-----

Add loadl group and user to 61cosi-ll:

```
cd /export/nim/61cosi-ll/usr/lpp/bos/inst_root
```

```
mount /export/nim/61cosi-ll/usr ./usr
```

```
chroot ./usr/bin/mkgroup -a loadl
```

```
chroot ./usr/sbin/lsgroup loadl
```

```
chroot ./usr/bin/mkuser pgrp=loadl groups=loadl home=/u/loadl loadl
```

```
chroot ./usr/sbin/luser loadl
```

- TBD!!!

3.0 Special Cases

3.1 Using other NIM resources.

When you run the **mknimimage** command to create a new xCAT *osimage* definition it will create default NIM resources and add their names to the *osimage* definition. It is also possible to specify additional or different NIM resources to use for the *osimage*. To do this you can use the “attr=val [attr=val ...]” option. These “attribute equals value” pairs are used to specify resource types and names to use when creating the the xCAT *osimage* definition. The “attr” must be a NIM resource type and the “val” must be the name of a previously defined NIM resource of that type, (ie. "<nim_resource_type>=<resource_name>").

For example, to create a diskless image and include *tmp* and *home* resources you could issue the command as follows. This assumes that the *mytmp* and *myhome* NIM resources have already been created by using NIM commands directly.

```
mknimimage -t diskless -s /dev/cd0 611cosi tmp=mytmp home=myhome
```

These resources will be added to the xCAT *osimage* definition. When you initialize a node using this definition the **mkdsklnode** command will include all the resources when running the “nim -o dkls_init” operation.

See the NIM documentation for more information on supported diskless resources.

3.2 Booting a “dataless” node.

AIX NIM includes support for “dataless” systems as well as “diskless”. NIM defines a dataless machine as one that has some local disk space that could be used for paging space and optionally the /tmp and /home. If you wish to use dataless machines you can create an xCAT *osimage* definition for them with the

mknimimage command. When creating the *osimage*, use the “-t” option to specify a type of “dataless”.

For example, to create an *osimage* definition for “dataless” nodes you could run the command as follows.

```
mknimimage -s /dev/cd0 -t dataless 53cosi
```

When the node is initialized to use this image the **mkdsklsnode** command will run the “nim -o dtls_init ..” operation.

See the NIM documentation for more information on the NIM support for dataless systems.

3.3 Specifying additional values for the NIM node initialization.

When you run the **mkdsklsnode** command to initialize diskless nodes the command will run the required NIM commands using some default values. If you wish to use different values you can specify them on the **mkdsklsnode** command line using the “attr=val [attr=val ...]” option. See the **mkdsklsnode man** page for the details of what attributes and values are supported.

For example, when **mkdsklsnode** defines the diskless node there are default values set for the “speed”(100) and “duplex”(full) network settings. If you wish to specify a different value for “speed” you could run the command as follows.

```
mkdsklsnode -i myosimage mynode speed=1000
```

4.0 Updating AIX diskless nodes using xCAT

This section describes how AIX diskless nodes can be updated using xCAT and AIX/NIM commands. It covers the switching of the node to a completely different image or to an updated version of the current image. It is not meant to be an exhaustive presentation of all options that are available to xCAT/AIX system administrators.

To update an AIX diskless node with new or additional software you must modify the NIM SPOT resource (operating system image) that the node is running.

Since you cannot modify a SPOT while a node is using it, you must either stop the nodes to update the image or create a new image for the nodes to use.

Stopping the nodes to do the updates means the nodes will be unusable for some period of time and there will be no easy way to back out an update if necessary. For these reasons the procedure described in this “How-To” will focus on creating a new image and rebooting the nodes with that image. The new image could be a completely new operating system image or it could be a copy of the the existing image that you can update as needed.

4.1 Create a new image

4.1.1 Create a new image from different source

In this case we create a new xCAT *osimage* definition with a new set of resources by running the xCAT **mknimimage** command with the source for the new resources. This is the same way you created the original xCAT *osimage* definition for the node.

When you run the command you must provide a source for the installable images. This can be the location of the source code or the name of another NIM *lpp_source* resource. You must also provide a name for the image you wish to create. This name will be used for the NIM SPOT resource definition as well as the xCAT *osimage* definition.

By default the NIM resources will be created in a subdirectory of */install/nim*. You can use the “-l” option to specify a different location.

For example, to create a diskless image called “*61cosi*” using the AIX product CDs as the source you could issue the following command.

```
mknimimage -t diskless -s /dev/cd0 61cosi
```

(This operation could take a while to complete!)

The command will create new NIM *lpp_source*, SPOT, dump, paging, and root resources. A new xCAT *osimage* definition will also be created, (called “*61cosi*”), which will contain the names of these resources.

You could also use the name of an existing NIM *lpp_source* resource as the source of a new *osimage* definition. For example, you could use a resource created for a previous *osimage* called *61cosi_lpp* to create a whole new *osimage* called *61cosi_updt* as follows.

```
mknimimage -t diskless -s 61cosi_lpp 61cosi_updt
```

The **mknimimage** command will display the contents of the new *osimage* definition when it completes.

This new image can now be updated and used to boot the node.

4.1.2 Copy an existing image

You can use the **mknimimage** command to create a copy of an image. For example, if the name of the currently running image is *61cosi* and you want make a copy of it to update, you could run the following command.

```
mknimimage -t diskless -i 61cosi 61cosi_updt
```

If a “-i ” value is provided then all the resources from the xCAT *osimage* definition (*61cosi*) will be used in the new *osimage* definition except the SPOT resource. The new SPOT resource will be copied from the one specified in the original definition and renamed using the new *osimage* name provided (*61cosi_updt*). A new xCAT *osimage* definition will also be created, called “*61cosi_updt*”, which will contain the names of these resources.

This new image can now be updated and used to boot the node.

4.2 Update the SPOT(COSI) (optional)

Once the SPOT is created you can update it in several ways.

- Install additional **installp** or **rpm** packages.
- Add or modify specific files, (such as /etc/inittab).
- Use the **chroot** command to run commands in the root file system contained in the SPOT/COSI.

The details for updating a SPOT are covered in the “Updating a NIM SPOT resource” section.

4.3 Verify the new image (optional)

To display the xCAT image definition run the xCAT **lsdef** command.

```
lsdef -t osimage -l -o 6lcosi
```

To get details for the NIM resource definitions use the AIX **lsnim** command. For example, if the name of your SPOT resource is "6lcosi" then you could get the details by running:

```
lsnim -l 6lcosi
```

To see the actual contents of a resource use "*nim -o showres <resource name>*".

For example, to get a list of the software installed in your SPOT you could run:

```
nim -o showres 6lcosi
```

4.4 Set up post boot scripts (optional)

- add list to “postscripts” node attribute
- copy post scripts to /install/postscripts directories
- TBD

4.5 Initialize the NIM diskless nodes

You can set up NIM to support a diskless boot of nodes by using the xCAT **mkdsklnode** command. This command uses information from the xCAT database and default values to run the appropriate NIM commands.

There are four basic situations where you would need to initialize a NIM diskless machine.

1. When you are booting a NIM diskless machine for the first time.
2. When you are booting a NIM machine that has been stopped so that you could update the current image.
3. When you want to switch a running node to a new image.
4. When you want to reboot a node using a different image by using an alternate NIM machine definition for a node. (This avoids having the node be down while the initialization step is completing.)

For either of the first two situations you can do the initialization of the nodes using the xCAT **mkdsklsnode** command as follows.

```
mkdsklsnode -i 61cosi node01,node09
```

If the “-i” value is not provided then the code checks the node definitions for the value of the "profile" attribute. If the “-i” value is provided then the command will set the “profile” attribute in the node definitions.

In the third situation you want to switch the nodes to use a new or updated image. You can use the "-s" option of the **mkdsklsnode** command to do this. With this option the **mkdsklsnode** command will stop the node to do the NIM uninitializing/reinitializing and therefore would result in additional down time for the nodes beyond the time for the node reboot.

For example, to switch the node named “*node29*” to a new image named “*611spot*” you could run the following command.

```
mkdsklsnode -s -i 611spot node29
```

The name of the image (“*611spot*”) is the xCAT *osimage* name which is also the name of the SPOT resource that was created for this *osimage* definition.

In the fourth scenario we want to initialize an xCAT diskless node by creating an alternate NIM machine definition for the same xCAT cluster node. This option allows you to do the NIM initialization step while the node is currently running.

Creating alternate NIM machine definitions is possible because the NIM name for a machine definition does not have to be the hostname of the node. This allows you to have multiple NIM machine definitions for the same node. Since all the NIM initialization of the alternate machine definition can be done while the node is running the downtime for the node is reduced to the time it takes to reboot.

For example, to initialize the xCAT node named “*node42*” to use the xCAT *osimage* named “*61cosi*” you could run the following command.

```
mkdsklsnode -n -i 61cosi node42
```

The naming convention for the new NIM machine name is "`<xcat_node_name>_<image_name>`", (Ex. "*node01_61spot*"). You could continue to create alternate machine definitions for each new image you wish to use for the node. The last NIM machine name that is initialized will determine what the node will use for the next boot.

Using the “-n” option will save time but it will also leave you with multiple alternate NIM machine definitions for the same node. If you wish to do go back to the “normal” naming convention, (using the xCAT node name as the NIM machine

name), you could run the **mkdsklsnode** command for the same node without the “-n” option. For example, in the previous example you got a NIM machine definition called “node42_61cosi”. If you wish to switch back to a NIM machine name of “node42” for the next update you could run **mkdsklsnode** as follows. (You may need the “-f” (force) option if the “node42” definition already exists.)

```
mkdsklsnode -f -i 611cosi node42
```

4.6 Verify node readiness (optional)

To verify that NIM has allocated the required resources for a node and that the node is ready for a network boot you can run the “**lsnim -l**” command. For example, to check node “node01” you could run the following command.

```
lsnim -l node01
```

In preparation for the network boot the NIM “dskls_init” operation configures *bootp*. At this point you can verify that the */etc/bootptab* file has an entry for each node you wish to boot. Also, it is recommended that you stop and restart the *inetd* service to ensure the new *bootp* configuration is loaded:

```
stopsrc -s inetd  
startsrc -s inetd
```

4.7 Initiate a network boot

Initiate a remote network boot request using the xCAT **rnetboot** command. For example, to initiate a network boot of all nodes in the group “*aixnodes*” you could issue the following command.

```
rnetboot aixnodes
```

NOTE: If you receive timeout errors from the **rnetboot** command, you may need to increase the default 60-second timeout to a larger value by setting *ppctimeout* in the site table:

```
chdef -t site -o clustersite ppctimeout=180
```

4.8 Verify the deployment

- As soon as the **rnetboot** command returns you can open a remote console to monitor the boot progress using the xCAT **rcons** command. This command requires that you have *conserver* installed and configured. To configure *conserver*, run:

```
makeconservercf
```

Kill the *conserver* daemon if it is running, and restart it:

```
conserver &
```

(You may need to add /opt/freeware/bin and /opt/freeware/sbin to your PATH first).

To start a console:

```
rcons node01
```

- You can use the AIX **lsnim** command to see the state of the NIM installation for a particular node, by running the following command on the NIM master:

```
lsnim -l <clientname>
```

- Retry and troubleshooting tips:
 - For p6 lpar, it may be helpful to bring up the HMC web interface in a browser and watch the lpar status and reference codes as the node boots.
 - Verify network connections
 - If the **rnetboot** returns “unsuccessful” for a node, verify that bootp and tftp is configured and running properly.
 - View /etc/bootptab to make sure an entry exists for the node.
 - Verify that the information in /tftpboot/<node>.info is correct.
 - Stop and restart inetd:

```
stopsrc -s inetd
```

```
startsrc -s inetd
```
 - Stop and restart tftp:

```
stopsrc -s tftp
```

```
startsrc -s tftp
```
 -
 - Verify NFS is running properly and mounts can be performed with this NFS server:
 - View /etc/exports for correct mount information.
 - Run the showmount and exportfs commands.
 - Stop and restart the NFS and related daemons:

```
stopsrc -g nfs
```

```
startsrc -g nfs
```
 - Attempt to mount a filesystem from another system on the network.
 - If the **rnetboot** operation is successful, but lsrim shows that the node is stuck at one of the netboot phases, you may need to redo your NIM definitions. Try the “short” approach first:

```
nim -F -o reset node01
```

```
nim -o dkls_init node01
```

```
rnetboot -f node01
```
 - If that doesn't work, you may need to delete the entire client definition from NIM and recreate it:

```
nim -F -o reset node01
```



```
nim -o deallocate -a root=root -a paging=paging -a dump=dump -a spot=61cosi node01  
nim -o remove node01  
mkdsklsnode -i 61cosi node01  
rnetboot -f node01
```

5.0 Cleanup

The NIM definitions and resources that are created by xCAT commands are not automatically removed. It is therefore up to the system administrator to do some clean up of unused NIM definitions and resources from time to time. (The NIM lpp_source and SPOT resources are quite large.) There are xCAT commands that can be used to assist in this process.

5.1 Removing NIM machine definitions

Use the xCAT **rmnsklsnode** command to remove all NIM machine definitions that were created for the specified xCAT nodes. This command will not remove the xCAT node definitions.

For example, to remove the NIM machine definition corresponding to the xCAT node named “node01” you could run the command as follows.

```
rmnsklsnode node01
```

The previous example assumes that the NIM machine definition is the same name as the xCAT node name. If you had used the “-n” option when you created the NIM machine definitions with **mkdsklsnode** then the NIM machine names would be a combination of the xCAT node name and the *osimage* name used to initialize the NIM machine. To remove these definitions you must provide the **rmnsklsnode** command with the name of the *osimage* that was used.

For example, to remove the NIM machine definition associated with the xCAT node named “node2” and the *osimage* named “61spot” you could run the following command.

```
rmnsklsnode -i 61spot node02
```

If the NIM machine is currently running or the machine definition was left in a bad state you can use the **rmnsklsnode** “-f” (force) option. This will stop the node and deallocate any resources it is using so the machine definition can be removed.

The **rmnsklsnode** command is intended to make it easier to clean up NIM machine definitions that were created by xCAT. You can also use the AIX **nim** command directly. See the AIX/NIM documentation for details.

5.2 Removing NIM resources

Use the xCAT **rmnimimage** command to remove all the NIM resources associated with a given xCAT *osimage* definition. The command will only remove a NIM resource if it is not allocated to a node. You should always clean up the NIM node definitions before attempting to remove the NIM resources. The command will also remove the xCAT *osimage* definition that is specified on the command line.

For example, to remove the “61spot” *osimage* definition along with all the associated NIM resources run the following command.

```
rmnimimage 61cosi
```

If necessary, you can also remove the NIM definitions directly by using NIM commands. See the AIX/NIM documentation for details.

6.0 Notes

6.1 Terminology

image

The term “image” is used extensively in this document. The precise meaning of an “image” will vary depending on the context in which the term is being used. In general you can think of an image as the basic operating system image as well as other resources etc. that are needed to boot a node. In most cases in this document we will be referring to an image as either an xCAT *osimage* definition or an AIX/NIM diskless image, (COSI).

osimage - This is an xCAT object that can be used to describe an operation system image. This definition can contain various types of information depending on what will be installed on the node and how it will be installed. The image definition is not node specific and can be used to deploy multiple nodes. It contains all the information that will be needed by the underlying xCAT and NIM support to deploy the node.

COSI - A Common Operating System Image is the name used by AIX/NIM to refer to a SPOT resource. From the NIM perspective this would be an AIX diskless image.

diskless node

The operating system is not stored on local disk. For AIX systems this means the file systems are mounted from a NIM server. NIM also supports the concept of a *dataless* system which has some limited disk space that can be used for certain file systems. See the “Special Cases” section below for information on using additional NIM features.

diskfull node

For AIX systems this means that the node has local disk storage that is used for the operating system. Diskfull AIX nodes are typically installed using the NIM **rte** or **mksysb** type install methods.

6.2 NIM diskless resources

The following list describes the required and optional resources that are managed by NIM to support diskless and dataless clients.

boot

Defined as a network boot image for NIM clients. The **boot** resource is managed automatically by NIM and is never explicitly allocated or deallocated by users.

SPOT

Defined as a directory structure that contains the AIX run-time files common to all machines. These files are referred to as the **usr** parts of the fileset. The **SPOT** resource is mounted as the **/usr** file system on diskless and dataless clients.

Contains the **root** parts of filesets. The **root** part of a fileset is the set of files that may be used to configure the software for a particular machine. These **root** files are stored in special directories in the **SPOT**, and they are used to populate the root directories of diskless and dataless clients during initialization.

The network boot images used to boot clients are constructed from software installed in the **SPOT**.

A **SPOT** resource is required for both diskless and dataless clients.

root

Defined as a parent directory for client **/** (**root**) directories. The client root directory in the **root** resource is mounted as the **/** (**root**) file system on the client.

When the resources for a client are initialized, the client **root** directory is populated with configuration files. These configuration files are copied from the **SPOT** resource that has been allocated to the same machine.

A **root** resource is required for both diskless and dataless clients.

This resource is managed automatically by NIM.

dump

Defined as a parent directory for client dump files. The client dump file in the **dump** resource is mounted as the dump device for the client.

A **dump** resource is required for both diskless and dataless clients.

This resource is managed automatically by NIM.

paging

Defined as a parent directory for client paging files. The client paging file in the **paging** resource is mounted as the paging device for the client.

A **paging** resource is required for diskless clients and optional for dataless clients.

This resource is managed automatically by NIM.

home

Defined as a parent directory for client **/home** directories. The client directory in the **home** resource is mounted as the **/home** file system on the client.

A **home** resource is optional for both diskless and dataless clients.

shared_home

Defined as a **/home** directory shared by clients. All clients that use a **shared_home** resource will mount the same directory as the **/home** file system.

A **shared_home** resource is optional for both diskless and dataless clients.

tmp

Defined as a parent directory for client **/tmp** directories. The client directory in the **tmp** resource is mounted as the **/tmp** file system on the client.

A **tmp** resource is optional for both diskless and dataless clients.

resolv_conf

This resource is a file that contains nameserver IP addresses and a network domain name.

It is copied to the **/etc/resolv.conf** file in the client's root directory.

A **resolv_conf** resource is optional for both diskless and dataless clients.

The AIX/NIM resources for diskless/dataless machines will remain allocated and the node will remain initialized until they are specifically unallocated and uninitialized.

6.3 NIM Commands

6.3.1 COSI commands

AIX provides commands that may be used to manage the SPOT (or COSI) resource. Refer to the AIX man pages for further details.

- **mkcosi** Create a COSI (SPOT) for a thin server (diskless or dataless client) to mount and use.

- **chcosi** Manages a Common Operating System Image (COSI).
- **cpcosi** Create a copy of a COSI (SPOT).
- **lscosi** List the properties of a COSI (SPOT).
- **rmcosi** Remove a COSI (SPOT) from the NIM environment.

6.3.2 Thin server commands

AIX provides several commands that can be used to manage diskless (also called thin server) nodes. See the AIX man pages for further details.

- **mkts** Create a thin server and all necessary resources.
- **lsts** List the status and software content of a thin server.
- **swts** Switch a thin server to a different COSI.
- **dbts** Perform a debug boot on a thin server.
- **rmts** Remove a thin server from the NIM environment.