

XCAT 2 DB2 Setup

07/28/10, 10:35:30 AM

1.0 Overview Setup DB2 on the Management Node.....	2
2.0 Install DB2 on the Management Node.....	3
2.1 Disk space needed to install DB2	3
2.2 Installation Steps.....	4
2.3 Installing the DB2 License.....	5
2.4 Installing Latest Fix Packs.....	6
3.0 Installation and Setup of DBD::DB2 Perl modules.....	6
3.1 perl-DBI.....	6
3.2 Build and Install DBD::DB2 code.....	6
4.0 Setting up the DB2 Server Instance.....	7
5.0 Start the DB2 Server	10
5.1 Increasing processor entitlement.....	10
5.2 DB2 Useful Commands.....	10
6.0 Create the xCAT Database.....	11
6.1 Restart the Instance to Apply the Changes.....	11
7.0 Migrate xCAT data to DB2	11
8.0 Setting up the DB2 Client on the Service Nodes.....	13
8.1 Install the DB2 Client software on the SN.....	13
8.2 Installation and Setup of DBD::DB2 Perl modules.....	14
8.3 Creating the Client Instance on the Service Node.....	14
8.4 Creating the catalog of the DB2 Server Node on the Service Node	16
8.5 Catalog the Server Instance Database on the Service Node.....	16
8.6 Test the Database Connection	16
9.0 Adding ODBC support (under construction).....	17
9.1 Setup the ODBC on the Management Node (DB2 Server).....	17
9.2 Setup ODBC on the Service Nodes.....	20
10.0 Installing xCAT on the Service Node.....	22
11.0 Removing xCAT from DB2.....	22
12.0 Removing DB2 from MN and SN.....	23
13.0 References.....	23
14.0 Diagnostics.....	23

1.0 Overview Setup DB2 on the Management Node

DB2 is supported with the xCAT 2.4 release or later.

DB2 is a product of IBM. To use it with xCAT, you will need access to a licensed version of the product, our document is for the DB2 Enterprise Server Edition (ESE)

Version 9.7. We support it on AIX61 TL5 or later and Linux p-series (TBD name releases here).

xCAT 2.5 should already be installed on the Management Node following the xCAT documentations. For AIX, the xCAT 6.1 dependency packages must be installed. (put link here). These packages support Perl 5.8.8 which is installed on the required AIX level (AIX61J- AIX61 TL5 (AIX 6.1.5.0)) or later.

The trial download of DB2 will not work with xCAT, because it does not support client accesses which is a requirement for service nodes.

Because the setup is rather complex, if you are going to use DB2 with xCAT, contact the xCAT development team, and we will work with you.

In this scenario, you will install the OS on your Management node, service node(s), setup the DB2 Client and then update the service node with the xCAT software.

Note: xCAT supports open source databases MySQL and Postgresql on Linux and AIX. Postgresql on AIX is xCAT 2.5 or later. There are setup docs for each of these databases on the xCAT web, and an automated setup script for MySQL (xCAT 2.3.3 or later) and Postgresql (xCAT 2.5 or later) .

One reason to migrate from the default SQLite database to DB2 with xCAT is for xCAT hierarchy using Service Nodes. DB2 provides the ability for remote access to the xCAT database on the Management node which is required by Service Nodes. SQLite does not support remote access to the database. MySQL, Postgresql and DB2 do provide this service. Refer to the xCAT Service Node documentation for more information.

Other programs or scenarios within your environment may also benefit from or require DB2. This document contains steps to install DB2, configure the server and client, create a database and populate it with your xCAT data.

Before using this document, you should have a general understanding of DB2. If necessary, review the installation and tutorial sections of the [DB2 Product documentation](#).

There are many [DB2 products](#), our documents will cover the install and setup of xCAT on [DB2 Enterprise Server Edition](#). This product supports the full range of function needed by xCAT on AIX and Linux. You will have to purchase this production from IBM. This document will cover the setup of DB2 on SLES 10 SP3 or AIX 6.1, or later releases of those products on p-Series hardware. This document tested on Service Nodes with diskfull installs. Because of the size (you will need 4 gigabytes of free space disk space) of the DB2 Client that is required to be installed on the Service Nodes, it is probably unrealistic to have diskless Service Nodes running DB2. It is also recommended not to run DB2 from an NFS mount,

so using Stalite is also not a good option. Basically you should plan on having a diskfull install on any node running the DB2 client code.

For more references: see the References section.

Note: with all the DB2 commands run below, be patient. Some take several minutes to complete , and some take several seconds to return the prompt, even after they say they have completed. Never kill a command while running. It can cost you hours of recovery work. (Been there, done that).

2.0 Install DB2 on the Management Node

If you already have DB2 installed you can skip to the section Installation and Setup of DBD::DB2 Perl modules.

[Obtain the DB2 Software](#) appropriate for you OS and hardware. Save the download for the install of the Client on the Service Nodes later. Most of these directions come from the [Installing Enterprise DB2](#) at the Product Information Center and the [Configuring and Managing BlueGene DB2 Setup Sections](#). We will be using a Command Line (manual) installation method, not the Web interface.

All of the following steps must be run logged into the Management Node (xcatmn) as **root**.

Note: You must also download the DB2® license file `db2ese_o.lic` (part number C14KVEN), which you activate after installing the DB2 server.

2.1 Disk space needed to install DB2

DB2 will need 4 gigabytes of disk space to download and untar the tarball and then build the product for the Server and Client code on the MN. This does not include the size of the database.

Because the DB2 source tarball is so large, you may want to untar it on a Server and have that NFS mounted to the Management Node and install it from the mount.

The same is true for the Service Nodes. It will install more slowly, but you will save disk space on your MN and you do not need it on the MN after the install.

Keep the source around though, because you are also going to have to install all your service nodes. The DB2 tarball contains both the Server and Client code as you will see in the instructions below.

- To copy the tarball and unzip and untar -- at least 4 gigabytes
- To install DB2 code (MN and SN) in /opt -- at least 1.5 gigabytes
- To create xcatdb database and instance on MN in /var – Need minimum of 465348KB to create, but the database will grow, so I would start with 1 gigabyte.

2.2 Installation Steps

- 1) To uncompress the image, copy the tar file or files to a temporary file system containing at least 2 gigabytes of free space, here we used **/db2source**. We will use the default install path `/opt/ibm/db2/V9.7 (linux)` or `/opt/IBM/db2/V9.7 (AIX)` for the database, which also must contain 2 gigabytes of free space.

- 2) Untar the download package:

```
cd /db2source
On Linux:
  zcat DB2_ESE_97_Linux_ipSeries.tar.gz | tar -xvf-
  or
On AIX:
  gunzip DB2_ESE_97_AIX.tar.gz
  tar -xvf DB2_ESE_97_AIX.tar
```

- 3) **If on Linux**, you are going to need to install [IBM XL C/C++ Advanced Edition V9.0 for Linux Runtime Environment Component](#) for the Linux Distro, you are using. Save this download for the install on the Service Nodes later.

- For our SLES 10 ppc system, we download the following:
`vacpp.rte.90.sles10.*.update.tar.gz` into `/db2source/vac9.0`.
- We unzip and untar the software:
`zcat vacpp.rte.90.sles10.*.update.tar.gz | tar -xvf-`
- Apply the updates, this installs the runtime libraries consisting of three RPMs – `vacpp.rte`, `xlsmp.rte`, and `xlsmp.msg.rte`.
`cd /db2source/vac9.0`
`rpm -Uvh *.rpm`

If on AIX, you are going to need to install `xlC` and the `vac` compiler.

- 4) Install DB2

```
cd /db2source/ese
./db2_install
```

You will be prompted with the following questions:

Default directory for installation of products - /opt/ibm/db2/V9.7

Do you want to choose a different directory to install
[yes/no] ?

Answer: no

Specify one of the following keywords to install DB2 products.

ESE
CLIENT
RTCL

Answer: ESE

Note: you may get a warnings about “SA MP Base Component cannot be installed or updated.” As long as you get no more than a warning at the end such as the following: WARNING: A minor error occurred while installing "DB2 Enterprise Server Edition" on this computer. Some features may not function correctly, followed by post setup instructions, it is ok.

2.3 Installing the DB2 License

The DB2 license file can be found in the db2/license directory on the installation CD or inside the installation directory. Depending on the product you have, the file is named db2ese.lic (Enterprise Server Edition). After installing the license, the system is ready to start the database. If you loaded a trial copy, you will be able to use it for 90 days without a license. The license will not be present in the install.

To install the license run the following command:

```
On Linux: /opt/ibm/db2/V9.7/adm/db2licm -a  
          /opt/ibm/db2/V9.7/license/db2ese.lic  
On AIX: /opt/IBM/db2/V9.7/adm/db2licm -a  
        /opt/IBM/db2/V9.7/license.db2ese.lic
```

DBI1402I License added successfully.

2.4 Installing Latest Fix Packs

For the latest Fix Packs for all DB2 version, go to this [download site](#).

3.0 Installation and Setup of DBD::DB2 Perl modules

3.1 perl-DBI

DBI (DataBase Interface) module and DBD::DB2 (DataBase Driver) are required on the Management Node for the xCAT code to interface with DB2.

Make sure perl-DBI is installed from the OS. Check by running:

```
rpm -qa | grep perl-DBI
```

3.2 Build and Install DBD::DB2 code

If you are using the Database level documented in the

The xCAT code uses the Perl DBD interface support for DB2. The level we have tested with is 1.78. If you have an older version, upgrade to 1.78. Some of the older versions do not support the function needed by xCAT. If you have 1.78 installed you can move on to Setting up the DB2 Server Instance.

For the build and installation of the Perl DBD::DB2 module follow the instructions below. You can read information about the Perl interface to DB2 at this site.

<http://www-01.ibm.com/support/docview.wss?rs=71&uid=swg21297335>

or

<http://www-01.ibm.com/support/docview.wss?rs=71&uid=swg21297335>

You will download the latest DBD:DB2 source code [from CPAN](#).

Note on AIX: you must install the VAC C/C++ compiler, on Linux gcc compiler

We will then compile and install it on your machine with the DB2 database you have installed.

```
mkdir ~/DBD
cd ~/DBD
download the current DBD source into ~/DBD
wget http://search.cpan.org/CPAN/authors/id/I/IB/IBMTORDB2/DBD-DB2-1.78.tar.gz
```

If wget is not available, ftp the file to the directory.

```
zcat DBD-DB2-1.78.tar.gz | tar -xvf-
cd ~/DBD/DBD-DB2-1.78
```

Build and install the Perl DBD:

On Linux:

```
DB2_HOME=/opt/ibm/db2/V9.7 DB2LIB=/opt/ibm/db2/V9.7/lib32 perl
Makefile.PL
```

On AIX:

```
DB2_HOME=/opt/IBM/db2/V9.7 perl Makefile.PL
```

For both AIX and Linux:

```
make ( on Linux you will get warnings)
make test
make install (if the tests look okay)
```

Note: if you are using perl 5.8.8 on AIX (AIX61J - AIX61 TL5 (AIX 6.1.5.0)

```
/usr/bin/perl -> /usr/opt/perl5/bin/perl5.8.8
```

The **make** may fail. Contact the xCAT development team. There is most likely a different Config.pm file needed in /usr/opt/perl5/lib/5.8.8/aix-thread-multi/ to produce the correct Makefile when running perl Makefile.PL.

The generated Makefile that is correct has the following line in it:
CDLFLAGS = -bE:/usr/opt/perl5/lib/5.8.8/aix-thread-multi/CORE/perl.exp -bE:/usr/opt/perl5/lib/5.8.8/aix-thread-multi/CORE/perl.exp -bE:/usr/opt/perl5/lib/5.8.8/aix-thread-multi/CORE/perl.exp -bE:/usr/opt/perl5/lib/5.8.8/aix-thread-multi/CORE/perl.exp

If the make does not fail and the Makefile looks correct, continue using the 5.8.8 Makefile.

4.0 Setting up the DB2 Server Instance

You can choose to use the db2sqlsetup script, instead of following this manual process. It is available in the xCAT 2.5 release. See man db2sqlsetup. The setup script will cover all the necessary steps for completing the process of setting up the Server and creating the xCAT database. You will be able to skip to the section Setting up the DB2 Client on the Service Nodes.

On the DB2 Server, the Management Node :This section takes you through the creation of the the DB2 Server Instance. The Server Instance will be called xcatdb. For more information on what is an Instance and what part it plays in DB2, read the following [DB2 information](#).

All of the following steps must be run logged into the Management Node as root.

- 1) Create a xcatdb user id and group for the DB2 instance. The home directory for the instance will be in /var/lib/db2.

On AIX:

```
mkgroup xcatdb
mkuser pgrp='xcatdb' home='/var/lib/db2' shell='/bin/ksh' xcatdb
```

On Linux:

```
groupadd xcatdb
useradd -d /var/lib/db2 -g xcatdb -m -s /bin/bash xcatdb
```

2) Set the xcatdb password

```
passwd xcatdb
```

Note: on AIX you are required to change the password when xcatdb first logs in. Log in and change to the permanent password. This password will be used by xCAT to access the database.

3) Add the following entry into /etc/services

Edit the /etc/services file and add the following (suggestion: insert above the references section)

```
#
# xcatd settings : Allow tcp communication for the instance, make sure port
# numbers do not conflict with existing entries.
#
DB2_xcatdb      60000/tcp
DB2_xcatdb_1   60001/tcp
DB2_xcatdb_2   60002/tcp
DB2_xcatdb_END 60003/tcp
db2c_xcatdb    50001/tcp # Port for server connection
```

4) Create the DB2 Server Instance

Note: you will need available space in /var/lib/db2 is 465348KB, for this to complete.

To create the xCAT DB2 Server Instance run the following as root:

on Linux

```
/opt/ibm/db2/V9.7/instance/db2icrt -a server -p db2c_xcatdb -s ese -u xcatdb xcatdb
```

on AIX


```
/opt/IBM/db2/V9.7/instance/db2icrt -a server -p db2c_xcatdb -s ese -u xcatdb xcatdb
```

5) Modify the DB2 Server Instance

As root:

```
cd /opt/ibm/db2/V9.7/instance on Linux
cd /opt/IBM/db2/V9.7/instance on AIX
./db2iset -g DB2_PARALLEL_IO=*
./db2iset -g DB2AUTOSTART=yes
./db2iset -g DB2_STRIPED_CONTAINERS=ON
```

```
su - xcatdb
> db2set -all
[i] DB2COMM=tcPIP
[g] DB2_STRIPED_CONTAINERS=ON
[g] DB2SYSTEM=c76a3l4vp01
[g] DB2INSTDEF=xcatdb
[g] DB2_PARALLEL_IO=*
[g] DB2AUTOSTART=yes
```

6) Set the db2 instance name and db2 home environment variables for root

For AIX as root:

```
vi /etc/profile
add the following line:
export DB2INSTANCE=xcatdb
```

For Linux as root:

```
cd /etc/profile.d
vi xcat.sh
add the following line:
export DB2INSTANCE=xcatdb
```

```
vi xcat.csh
add the following line:
setenv DB2INSTANCE "xcatdb"
```

Note: either logout and back in or set the environment variable manually for root:

```
export DB2INSTANCE=xcatdb
```

5.0 Start the DB2 Server

To start the server, you must logon as the xcatd instance id, create previously.

```
su - xcatdb
```

```
xcatdb@c76a314vp01:~> db2start
01/27/2010 19:48:08      0      0      SQL1063N  DB2START processing was
successful.
SQL1063N  DB2START processing was successful.
```

If you need to stop the database, use

```
xcatdb@c76a314vp01:~> db2stop
or
xcatdb@c76a314vp01:~> db2stop force
```

5.1 Increasing processor entitlement

After the database is started, you might want to increase the processor entitlement for DB2. Check the section "[Increasing processor entitlement](#)" for information on customizing you system.

5.2 DB2 Useful Commands

Note: path IBM for AIX, ibm for Linux

These commands, you run as root:

- Remove an instance:/opt/ibm/db2/V9.7/instance/db2idrop xcatdb
- If you have problems removing an instance use:
/opt/ibm /db2/V9.7/instance/db2iset -d xcatdb
- Show all instances:/opt/ibm/db2/V9.7/instance/db2ilist

These command, you run as xcatdb:

- db2 connect to xcatdb (connect to database) from Server
- db2 connect to xcatdb user xcatdb from Client
- db2 drop database xcatdb (drop the database)
- db2 list tables
- db2 describe table site
- db2 drop table site
- db2stop
- db2stop force
- db2start
- db2 (enter interactive admin session)
- db2 -t (enter interactive admin session where sql must end in ;)
- quit (quit out of interactive admin session)

6.0 Create the xCAT Database

We will create one database "xcatdb", it will be store in the "xcatdb" Instance home directory which is /var/lib/db2.

```
su - xcatdb
```

In your xCAT install `/opt/xcat/share/xcat/tools/createdb.sql`, is a script that you can run to create the xcatdb database. Run the following:

```
db2 -tvf /opt/xcat/share/xcat/tools/createdb.sql
```

Note: be patient, it takes a while. You may also investigate the default attributes of the database that we chose in this setup scripts and change according to your system needs.

6.1 Restart the Instance to Apply the Changes

```
su - xcatdb ( if not already there)
db2 connect reset
db2 force applications all; db2 terminate;
db2stop
db2start
exit
```

7.0 Migrate xCAT data to DB2

If you are using the `db2setup` script (TBD), this section will automatically be done for you. See `man db2setup`. (TBD)

1. You must backup your xCAT data before populating the DB2 database. There are required default entries that were created in the SQLite database when the xCAT RPMs were installed on the Management Node, and they must be migrated to the new DB2 database.

```
mkdir -p ~/xcat-dbback
dumpxCATdb -p ~/xcat-dbback
```

Note: if you get an error, like “Connection failure: IO::Socket::SSL: connect: Connection refused at....,” make sure your xcatd daemon is running.

2. **Creating the `/etc/xcat/cfgloc` file** tells xcat what database to use. If the file does not exist, it uses by default SQLite, which is setup during the xCAT

install by default. The information you put in the files, corresponds to the information you setup when you configured the database. Create a file called */etc/xcat/cfgloc* and populate it with the following line:

```
DB2:xcatdb|xcatdb|ppslab09
```

```
DB2:<databasename>|<instancename>|<instancepassword>
```

The first variable is the database name *xcatdb* that was setup. The second variable is the name of the Instance. The password must match the password of your DB2 Instance “*xcatdb*” userid.

Finally change permissions on the file, so only root can read, to protect the password.

```
chmod 0600 /etc/xcat/cfgloc
```

3. Stop the *xcatd* daemon, so no database actions will occur while you are migrating the data to DB2.

On AIX: `stopsrc -s xcatd`

On Linux: `service xcatd stop`

4. Restore your database to DB2. Use bypass mode to run the command because the daemon is no longer running. This can take a while.

```
XCATBYPASS=1 restorexCATdb -p ~/xcat-dbback
```

*Note: If you still have errors that you can not resolve, you can go back to using *SQLite*, by moving */etc/xcat/cfgloc* to */etc/xcat/cfgloc.save* and restarting *xcatd*.*

5. Start the *xcatd* daemon using the DB2 database.

On AIX: `startsrc -s xcatd`

On Linux: `service xcatd restart`

6. *Test the database*

```
tabdump site
```

8.0 Setting up the DB2 Client on the Service Nodes.

8.1 Install the DB2 Client software on the SN

Follow the instructions in Install DB2 on the Management Node, to install the DB2 code on your Service Node (SN), up to the point Install DB2 where you actually install DB2. You are only going to install the Client on the SN. Note you probably do not have to download the DB2 code again, if you have saved the downloads from the Server install.

Note: the disk space needed as documented in 3Disk space needed to install DB2 .

Install DB2:

```
cd /db2source/ease
./db2_install
```

You will be prompted with the following questions:

```
Default directory for installation of products - /opt/ibm/db2/
V9.7
```

```
Do you want to choose a different directory to install
[yes/no] ?
```

Answer: no

Specify one of the following keywords to install DB2 products.

```
ESE
CLIENT
RTCL
```

Answer: CLIENT

8.2 Installation and Setup of DBD::DB2 Perl modules

As you did on the Management Node (MN), the Perl DB2 DBD will have to be installed on all Service nodes. If your Service Nodes are at the same OS level as

your Management node, you can mount the directory from the MN to the Service Node and just run the install.

For installing the DBD:DB2 DBI from a mount:

On the MN:

```
export ~/DBD read-only
```

On the SN:

```
mkdir /mnt2
```

```
mount xx.xxx.xxx.xxx:~/DBD /mnt2
```

```
cd /mnt2/DBD-DB2-1.78
```

```
make test ( if no errors continue with the make install)
```

```
make install
```

```
umount or umount /mnt2
```

For installing the DBD:DB2 DBI from the source code:

Follow the instructions in Installation and Setup of DBD::DB2 Perl modules.

8.3 Creating the Client Instance on the Service Node

You can choose to use the db2sqlsetup script, instead of following this manual process. It is available in the xCAT 2.5 release. See man db2sqlsetup. It will automatically setup the client. After you finish running the script to setup the client, you can proceed to Test the Database Connection .

This section takes you through the creation of the the DB2 Client Instance on the Service Node. The Client Instance will be called xcatdb.

For more information on what is an Instance and what part it plays in DB2, read the following [DB2 information](#).

All of the following steps must be run logged into the Service Node as root. We will want to create the group and userid with the same gid and uid as was assigned on the Management Node.

- 1) On the MN, read the gid and uid of the xcatdb group and userid.

```
cat /etc/passwd | grep xcatdb
```

```
xcatdb:!:212:205:./var/lib/db2:/bin/ksh
```

The first number (212) is the uid, the second (205) is the gid.

- 2) Create a xcatdb user id and group for the DB2 client instance. The home directory for the instance will be in /var/lib/db2 as on the MN.
Note: make sure the uid of the userid and group match the uid on the Management Node. The numbers are from step (1).

On AIX:

```
mkgroup id=205 xcatdb
mkuser pgrp='xcatdb' id=212
home='/var/lib/db2' shell='/bin/ksh' xcatdb
```

On Linux:

```
groupadd -g 205 xcatdb
useradd -d /var/lib/db2 -g xcatdb -u 212 -m -s
/bin/bash xcatdb
```

- 3) Set the xcatdb password

```
passwd xcatdb
```

Note: on AIX you are required to change the password when xcatdb first logs in, if root sets it. Recommend you use the same as was assigned on the MN.

- 4) **Add the following entry into /etc/services on the Service Node**

Edit the /etc/services file and add the following (suggestion: insert above the references section)

note this must match what is in /etc/services on the Management/DB2 Server.
Again make sure matching port is not used on both machines.

```
db2c_xcatdb 50001/tcp # Port for DB2 Server Connect
```

- 5) Create the DB2 Client Instance

To create the xCAT DB2 Client Instance run the following:

On Linux:

```
/opt/ibm/db2/V9.7/instance/db2icrt -s client xcatdb
```

On AIX:

```
/opt/IBM/db2/V9.7/instance/db2icrt -s client xcatdb
```

8.4 Creating the catalog of the DB2 Server Node on the Service Node

Now we will setup the Client on the Service Node to access the database on the Management Node (mn) using xcatdb instance on the Service Node:

```
su - xcatdb
```

```
db2 catalog tcpip node mn remote 9.114.113.203 server db2c_xcatdb  
(note: port must match what is in /etc/services)  
db2 terminate ( refreshes cache)
```

Note: 9.114.113.203 must be an address or resolvable hostname that the Service Node can access the Management Node.

8.5 Catalog the Server Instance Database on the Service Node

Next on the Service Node, we will catalog the xcatdb database and it's location on the mn.

```
su - xcatdb ( if not already there)  
db2 catalog db xcatdb as xcatdb at node mn  
db2 terminate ( refreshes cache)
```

For more information: See
<http://publib.boulder.ibm.com/infocenter/db2luw/v8/index.jsp?topic=/com.ibm.db2.udb.doc/core/r0001944.htm>

8.6 Test the Database Connection

```
su - xcatdb (if not already there)
```



```
db2 connect to xcatdb user xcatdb
```

You will be prompted for xcatdb's password. After entering it you should see something similar to this:

```
Database Connection Information Database server = DB2/LINUXPPC64 9.7.1
SQL authorization ID = XCATDB
Local database alias = XCATDB
```

Close the connection with -

```
db2 connect reset
exit
```

9.0 Adding ODBC support (under construction)

You only need to follow the steps in this section on adding ODBC support, if you plan to develop C, C++ database applications on the database or run such applications (like LoadLeveler). Otherwise skip to the next section.

As of xCAT 2.5 or later, you can use `db2sqlsetup` command in xCAT to perform the operations in steps 2 and 3 below. See manpage for `db2sqlsetup`.

More information about the IBM DB2 Driver for ODBC and CLI is found in

<http://publib.boulder.ibm.com/infocenter/db2luw/v9/index.jsp?topic=/com.ibm.db2.udb.apdv.cli.doc/doc/c0023378.htm>

9.1 Setup the ODBC on the Management Node (DB2 Server)

1. Install ODBC package and set up the DB2 driver .

On AIX: You need the *unixODBC* packages

included in the *dep-aix-xxxx.tar.gz* file. The *.gz* file was download when the xCAT Management Node was setup. To install the package, go to the directory where the *gz* file was untared and use the following command:

```
rpm -i unixODBC-*
```

When a new a new DB2 instance is created on AIX, DB2 places a copy of the ODBC DB2 driver into the database instance directory: `<DB2INSTANCE_HOME>/sqllib/lib/libdb2.a`

As of xCAT 2.5 or later, you can use db2sqlsetup command in xCAT to perform the operations in steps below. See manpage for db2sqlsetup.

The unixODBC Driver Manager loads the DB2 Driver dynamically so the shared object must be extracted from the driver. To do this use the following commands:

```
cd /var/lib/db2/sqllib/lib  
ar -x libdb2.a
```

This produces a shr.o. Rename this file to libdb2.so.
mv shr.o libdb2.so

On Linux: The unixODBC package come as part of the OS. Refer to xCAT Top Doc for how to get packages from the distro.

```
rpm -i unixODBC-*
```

2. To configure ODBC you need to make changes to the *odbcinst.ini* and *odbc.ini* files so that ODBC works with the xCAT database. First update the *odbcinst.ini* file with the correct driver name.

On AIX, RH and Fedora:

For the Driver, enter the path name of the shared object you created:

```
vi /etc/odbcinst.ini
```

```
[DB2]  
Description = DB2 Driver  
Driver = /var/lib/db2/sqllib/lib/libdb2.so  
FileUsage = 1
```

```
DontDLClose = 1
```

On SLES: (TBD, if supported)

```
vi /etc/unixODBC/odbcinst.ini
```

```
[DB2]  
Description = DB2 Driver  
Driver = /var/lib/db2/sqlllib/lib/libdb2.so  
FileUsage = 1  
DontDLClose = 1
```

Then update the *odbc.ini* files with the DSN information for ODBC. Use DATABASE instance name as defined in the */etc/xcat/cfgloc* file.

On AIX, (Redhat to be tested):

```
vi /etc/odbc.ini
```

```
[xcatdb]  
Driver = DB2  
DATABASE = xcatdb
```

On SLES (to be tested. If supported)

```
vi /etc/unixODBC/odbc.ini
```

```
[xcatdb]  
Driver = DB2  
DATABASE = xcatdb
```

3. Put the xcatadmin id and password for xcatdb database on the root's home directory so that user root will not have to specify them when accessing the database through ODBC. The DATABASE, USER and PASSWORD must match was put in the */etc/xcat/cfgloc* file.

```
vi ~/.odbc.ini
```

```
[xcatdb]
DATABASE = xcatdb
USER = xcatdb
PASSWORD = xcat201
```

Update the permissions for root only read of the file.

```
chmod 0600 .odbc.ini
```

9.2 Setup ODBC on the Service Nodes

Skip this step, if there are no service nodes in the cluster.

Note: You can use the `db2sqlsetup` script to setup your service nodes, if xCAT is installed instead of the following manual steps. See `man db2sqlsetup` for with the `-C -o` option.

If there are service nodes in the cluster you need to install

unixODBC and the DB2 driver on them and modify the ODBC configuration files just as we did in step 1 and 2. You should have already installed and setup the DB2 Client code on the Service Nodes as documented in Setting up the DB2 Client on the Service Nodes.

Install the DB2 driver into the same directory as on the management node, so the `odbcinst.ini` file can be the same on the management and service nodes..

xCAT has utilities to install additional software on the nodes. To install ODBC on to the service nodes, refer to the following documents for details:

AIX: [xCAT2onAIXUpdates.pdf](#)

Linux: [xCAT2-updatenode.pdf](#)

To setup the ODBC configuration files, just sync the files to the service nodes from the ones setup on the Management Node.

The service in the following command is the node group name for all the service nodes.

On AIX:

```
xdbc service -v /etc/odbcinst.ini /etc/odbcinst.ini
xdbc service -v /etc/odbc.ini /etc/odbc.ini
xdbc service -v /.odbc.ini /.odbc.ini
```

On RH and Fedora:

```
xdbc service -v /etc/odbcinst.ini /etc/odbcinst.ini
xdbc service -v /etc/odbc.ini /etc/odbc.ini
xdbc service -v /root/.odbc.ini /root/.odbc.ini
```

On SLES

```
xdbc service -v /etc/unixODBC/odbcinst.ini /etc/unixODBC/odbcinst.ini
xdbc service -v /etc/unixODBC/odbc.ini /etc/unixODBC/odbc.ini
xdbc service -v /root/.odbc.ini /root/.odbc.ini
```

You will have to setup one additional file on the Service Node(client):

```
vi /var/lib/db2/sqllib/cfg/db2cli.ini
```

Change the following stanza:

```
[tstcli1x]
uid=userid
pwd=password
```

to

```
[xcatdb]
uid=xcatdb
pwd=xcat201
```

5. Test the ODBC connection.

On AIX, as root: `/usr/local/bin/isql -v xcatdb`

or as non-root user: `/usr/local/bin/isql -v xcatdb xcatdb <passwd>`

On Linux, as root: `/usr/bin/isql -v xcatdb`

or as non-root user: `/usr/bin/isql -v xcatdb xcatadmin xcat201`

```
/usr/local/bin/isql -v xcatdb
```

```
+-----+
| Connected! |
| |
| sql-statement |
| help[tablename] |
| quit |
+-----+
SQL> LIST TABLES;
+-----+
| Tables_in_xcatdb |
|-----|
| . |
| networks |
| nodelist |
| site |
| . |
| . |
+-----+
SQL> DESCRIBE table site;
+-----+-----+-----+-----+-----+
| Field | Type | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+
| key | varchar(128) | NO | PRI | | |
| value | text | YES | | NULL | |
| comments | text | YES | | NULL | |
| disable | text | YES | | NULL | |
+-----+-----+-----+-----+-----+
SQL > quit;
```

10.0 Installing xCAT on the Service Node

Now that the DB2 database is setup you can install xCAT on the Service Node. Use the following references for setting up your Service Nodes:

- [Setting up Hierarchy in xCAT](#)
- [Setting up an AIX Hierarchical Cluster](#)

11.0 Removing xCAT from DB2

To remove the database, first back it up.

```
mkdir -p ~/xcat-dbback  
dumpxCATdb -p ~/xcat-dbback
```

1. stop the xcatd daemon
2. Now remove the database.

```
su - xcatdb  
>db2 drop database xcatdb;
```

3. remove /etc/xcat/cfgloc file (points xCAT to DB2)
4. Install the DB2 database into SQLite

```
XCATBYPASS=1 restorexCATdb -p ~/xcat-dbback
```

5. start xcatd

12.0 Removing DB2 from MN and SN

To remove DB2 from your MN and Service Node after removing xCAT from the DB, do the following: (note path is IBM for AIX, ibm for Linux)

On the Service Node as root:

- 1) Remove the instance: (if will not remove, su - xcatdb on the MN and db2stop, then try again).
/opt/IBM/db2/V9.7/instance/db2idrop xcatdb
- 2) Check to see if no instance:
/opt/IBM/db2/V9.7/instance/db2ilist
- 3) Remove the DB2 (this takes a while and removes the db2 installed):
/opt/IBM/db2/V9.7/install/db2_deinstall -a
- 4) remove instance port from /etc/services

- ```
vi /etc/services
delete entry: db2c_xcatdb1 50001/tcp # Port for server connection
```
- 5) remove xcatdb user and xcatdb group
  - 6) remove export DB2INSTANCE=xcatdb from /etc/profile on AIX, or /etc/profile.d/xcat.sh or xcat.csh on Linux.

#### On the Management Node

- 1) su – xcatd and stop the database db2stop
- 2) Remove the instance as root  
/opt/IBM/db2/V9.7/instance/db2idrop xcatdb
- 3) Check to see if no instance:  
/opt/IBM/db2/V9.7/instance/db2ilist
- 4) Remove DB2 ( this takes a while, this removes the DB2 install)  
/opt/IBM/db2/V9.7/install/db2\_deinstall -a
- 5) Remove xcat entries in /etc/services  
db2c\_xcatdb 50001/tcp # Port for server connection
- 6) remove xcatdb user and xcatdb group
- 7) remove export DB2INSTANCE=xcatdb from /etc/profile on AIX, or /etc/profile.d/xcat.sh or xcat.csh on Linux.

## 13.0 References

- *Configuring and Managing BlueGene* [DB2 Setup Sections](#)
- [MySQL to DB2 migration](#)
- [Setting up the DB2 Client](#)
- [DB2 Survival Guide](#)
- [DBD:DB2 pod](#)
- [DB2 Deployment Guide](#)
- [DB2 Perl Database Interface](#)
- [DBI mail archives](#)
- [Perl Programming with DB2](#)

## 14.0 Diagnostics

- 1) “Total Environment Allocation Failure” when running xCAT command to the database, such as tabdump.  
echo \$DB2INSTANCE should be xcatdb  
Usually loss of critical DB2 Env Var settings for the following:  
DB2INSTANCE=xcatdb ( most important)  
CUR\_INSTHOME=/var/lib/db2  
DB2DIR=/opt/ibm/db2/V9.7



INSTHOME=/var/lib/db2

See: [http://www.perlmonks.org/?node\\_id=682626](http://www.perlmonks.org/?node_id=682626)

See: Set the db2 instance name and db2 home environment variables for root

## 2) Set diagnostics level in database

You can up the diagnostics level and watch for database errors in the `~/sql/lib/db2dump/db2diag.log` and `xcatdb.nfy` under the `xcatdb` instance home directory on the DB2 Server.

Run the following to increase the diagnostics level. Note: this should be set back to level 3 after diagnosing the problem, because it affects DB performance.

On the MN:

```
stop xcatd
su - xcatdb
db2 update dbm cfg using diaglevel 4
db2stop
db2start
```