

xCAT 2.0 Roadrunner Cookbook

5/8/2008

Table of Contents

1.0 Release Description	3
2.0 Installing the Management Node	3
2.1 Download Fedora 8 and Create Repository	3
2.2 Downloading and Installing xCAT 2.0	4
2.2.1 If Your Management Node Has Internet Access:	4
2.2.1.1 Download Repo Files	4
1.1.1.1 Set Up Repo File for Fedora Site	4
2.2.2 If Your Management Node Does Not Have Internet Access:	5
2.2.2.1 Download xCAT2.0 and Its Dependencies	5
2.2.2.2 Get Fedora 8 OSS dependencies	5
2.2.2.3 Setup YUM repositories for xCAT and Dependencies	6
2.2.3 Install xCAT 2.0 software & Its Dependencies	6
2.2.4 Test xCAT installation	6
2.2.5 Update xCAT 2.0 software	6
2.2.6 Setup Yum for Fedora8 Node Installs	6
3.0 xCAT Hierarchy using Service nodes	7
3.1 Switching to PostgreSQL Database	7
3.2 Define the service nodes in the database	10
3.2.1 Define Service Nodes and bmc in nodelist table	10
3.2.2 Define Service Nodes in noderes table	10
3.2.3 Define Service Nodes in ipmi table	10
3.2.4 Define Service Nodes in nodehm table	10
3.2.5 Define Service Nodes in nodetype table	10
3.2.6 Set Necessary Attributes in site Table	11
3.2.7 Define Service Node OS and Profile attributes	11
4.0 Setup Services	11
4.1 Setup networks Table	11
4.2 Setup DNS	11
4.3 Define AMMs as nodes	12
4.4 Setup AMM	12
4.5 Startup TFTP	13
5.0 Define Compute Nodes in the Database	13
5.1 Setup the nodelist Table	13
5.2 Set Up the nodehm table	13
5.3 Set Up the mp Table	14
5.4 Setup Conserver	14
5.5 Setup the noderes Table	14
5.5.1 Sample noderes table	15

5.5.2 Setting up which services run on the Service Nodes	15
5.6 Setup nodetype table	15
5.6.1.1 Sample nodetype table	15
5.7 Setup passwords in passwd table	16
5.8 Verify the tables	16
5.9 Setup deps Table for proper boot sequence	16
5.10 Set Up Postscripts to be Run on the Nodes	16
5.11 Get MAC addresses	16
5.12 Setup DHCP	17
6.0 Build the service node stateless image	17
6.1 Configure the Service Node BMCs??	18
6.2 Install the Service Nodes	18
6.3 Test Service Node installation	18
7.0 iSCSI Install QS22 Blade	19
7.1 Build QS22 Stateless image	20
7.2 Boot the QS22 Stateless image	20
7.3 To Update QS22 Stateless image	21
7.4 Build and Install QS22 Compressed Image	22
7.4.1 Build aufs	22
7.4.2 Generate the compressed image	22
7.4.3 Pack and install the compressed image	23
7.4.4 Check Memory Usage	23
7.4.5 To Switch a Compute Blade to iSCSI for More Setup	23
8.0 Build LS21 Stateless image	24
8.1 To Update the LS21 Stateless Image Later On	25
8.2 Build and Install LS21 Compressed Image	25
8.2.1 Build aufs	26
8.2.2 Generate and pack the compressed image	26
8.2.3 Install the image	26
8.2.4 Check Memory Usage	26
9.0 Building QS22 Image for 64K pages	27
9.1 Rebuild aufs	28
9.2 Test unsquashed:	28
9.2.1 Check memory	28
9.3 Test squash	29
9.3.1 Check memory	29
9.4 To Switch Back to 4K Pages	29
10.0 Using NFS Hybrid for the Diskless Images	30
11.0 Installing OpenLDAP	34
11.1 Setup LDAP Server	34
11.1.1 Install the LDAP rpms	35
11.1.2 Configure LDAP	35
11.1.3 Migrate Users	36
11.1.4 Add a User to LDAP	37
1.1.2 Set ibm4 userid password	38
11.2 Setup LDAP Client	38
11.2.1 Install LDAP into the Image	38

11.2.2 Update the LDAP Configuration in the Image	38
11.2.3 Build the Image and Install	39
11.2.4 Test LDAP Client	39
12.0 Setup Hierarchical LDAP	40
13.0 Install Torque	40
13.1 Setup Torque Server	40
13.2 Configure Torque	40
13.3 Define Nodes	40
13.4 Setup and Start Service	41
13.5 Install pbsstop	41
13.6 Install Perl Curses for pbsstop	41
13.7 Create a Torque Default Queue	41
13.8 Setup Torque Client (x86_64 only)	41
13.8.1 Install Torque	41
13.8.2 Configure Torque	42
13.8.2.1 Set Up Access	42
13.8.2.2 Set Up Node to Node ssh for Root	42
13.8.3 Pack and Install image	42
14.0 Setup Moab	42
14.1 Install Moab	42
14.2 Configure Moab	43
14.2.1 Start Moab	43
15.0 References	43

1.0 Release Description

xCAT 2.0 is a complete rewrite of xCAT 1.2/1.3, implementing a new architecture. See the xCAT2.0 Cookbook for more details about the 2.0 product: <http://xcat.svn.sourceforge.net/svnroot/xcat/xcat-core/trunk/xCAT-client-2.0/share/doc/xCAT2.0.pdf>. All commands are client/server, authenticated, logged and policy driven. The clients can be run on any OS with Perl, including Windows. The code has been completely rewritten in Perl, and table data is now stored in a relational database.

2.0 Installing the Management Node

Before beginning, ensure that your networks are setup correctly.

2.1 Download Fedora 8 and Create Repository

1. Get Fedora ISOs and place in a directory, for example /root/xcat2:

```
mkdir /root/xcat2
cd /root/xcat2
wget
```

```
ftp://download.fedora.redhat.com/pub/fedora/linux/releases/8/Fedora/x86\_64/iso/Fedora-8-x86\_64-DVD.iso
```

```
wget
```

```
ftp://download.fedora.redhat.com/pub/fedora/linux/releases/8/Fedora/ppc/iso/  
Fedora-8-ppc-DVD.iso
```

2. Create YUM repository for Fedora RPMs:

```
mkdir /root/xcat2/fedora8  
mount -r -o loop /root/xcat2/Fedora-8-x86_64-DVD.iso /root/xcat2/fedora8
```

```
cd /etc/yum.repos.d  
mkdir ORIG  
mv fedora*.repo ORIG
```

Create fedora.repo with contents:

```
[fedora]  
name=Fedora $releasever - $basearch  
baseurl=file:///root/xcat2/fedora8  
enabled=1  
gpgcheck=0
```

3. Install createrepo:

```
yum install createrepo
```

2.2 Downloading and Installing xCAT 2.0

2.2.1 If Your Management Node Has Internet Access:

2.2.1.1 Download Repo Files

YUM can be pointed directly to the xCAT download site.

```
cd /etc/yum.repos.d  
wget http://xcat.sf.net/yum/core-snap/xCAT-core-snap.repo  
wget http://xcat.sf.net/yum/dep-snap/rh5/x86\_64/xCAT-dep-snap.repo
```

1.1.1.1 Set Up Repo File for Fedora Site

Create fedora-internet.repo:

```
[fedora-everything]  
name=Fedora $releasever - $basearch  
failovermethod=priority  
#baseurl=http://download.fedora.redhat.com/pub/fedora/linux/releases/  
$releasever/Everything/$basearch/os/  
mirrorlist=http://mirrors.fedoraproject.org/mirrorlist?repo=fedora-  
$releasever&arch=$basearch  
enabled=1  
gpgcheck=1  
gpgkey=file:///etc/pki/rpm-gpg/RPM-GPG-KEY-fedora file:///etc/pki/rpm-gpg/RPM-GPG-  
KEY
```

Continue now at step Install xCAT 2.0 software & Its Dependencies.

2.2.2 If Your Management Node Does Not Have Internet Access:

2.2.2.1 Download xCAT2.0 and Its Dependencies

Note: do the wget's on a machine with internet access and copy the files to the management node.

```
cd /root/xcat2
wget http://xcat.sf.net/yum/core-rpms-snap.tar.bz2
wget http://xcat.sf.net/yum/dep-rpms-snap.tar.bz2
tar jxvf core-rpms-snap.tar.bz2
tar jxvf dep-rpms-snap.tar.bz2
```

2.2.2.2 Get Fedora 8 OSS dependencies

```
cd /root/xcat2/dep-snap/rh/x86_64

wget
http://download.fedora.redhat.com/pub/fedora/linux/releases/8/Everything/x86\_64/os/Packages/perl-Net-SNMP-5.2.0-1.fc8.1.noarch.rpm
wget
http://download.fedora.redhat.com/pub/fedora/linux/releases/8/Everything/x86\_64/os/Packages/perl-XML-Simple-2.17-1.fc8.noarch.rpm
wget
http://download.fedora.redhat.com/pub/fedora/linux/releases/8/Everything/x86\_64/os/Packages/perl-Crypt-DES-2.05-4.fc7.x86\_64.rpm
wget
http://download.fedora.redhat.com/pub/fedora/linux/releases/8/Everything/x86\_64/os/Packages/net-snmp-perl-5.4.1-4.fc8.x86\_64.rpm
wget
http://download.fedora.redhat.com/pub/fedora/linux/releases/8/Everything/x86\_64/os/Packages/ksh-20070628-1.1.fc8.x86\_64.rpm
wget
http://download.fedora.redhat.com/pub/fedora/linux/releases/8/Everything/x86\_64/os/Packages/perl-IO-Socket-INET6-2.51-2.fc8.1.noarch.rpm
wget
http://download.fedora.redhat.com/pub/fedora/linux/releases/8/Everything/x86\_64/os/Packages/dhcp-3.0.6-10.fc8.x86\_64.rpm
wget
http://download.fedora.redhat.com/pub/fedora/linux/releases/8/Everything/x86\_64/os/Packages/syslinux-3.36-7.fc8.x86\_64.rpm
wget
http://download.fedora.redhat.com/pub/fedora/linux/releases/8/Everything/x86\_64/os/Packages/mtools-3.9.11-2.fc8.x86\_64.rpm
wget
http://download.fedora.redhat.com/pub/fedora/linux/releases/8/Everything/x86\_64/os/Packages/expect-5.43.0-9.fc8.x86\_64.rpm
wget
http://download.fedora.redhat.com/pub/fedora/linux/releases/8/Everything/x86\_64/os/Packages/perl-DBD-SQLite-1.12-2.fc8.1.x86\_64.rpm
wget
http://download.fedora.redhat.com/pub/fedora/linux/releases/8/Everything/x86\_64/os/Packages/perl-Expect-1.20-1.fc8.1.noarch.rpm
```

```
wget
http://download.fedora.redhat.com/pub/fedora/linux/releases/8/Everything/x86\_64/
os/Packages/perl-IO-Tty-1.07-2.fc8.1.x86\_64.rpm
wget
http://mirrors.usc.edu/pub/linux/distributions/fedora/linux/releases/8/Everythin
g/x86\_64/os/Packages/scsi-target-utils-0.0-1.20070803snap.fc8.x86\_64.rpm
wget
http://download.fedora.redhat.com/pub/fedora/linux/releases/8/Everything/x86\_64/
os/Packages/perl-Net-Telnet-3.03-5.1.noarch.rpm
```

2.2.2.3 Setup YUM repositories for xCAT and Dependencies

```
cd /root/xcat2/dep-snap/rh5/x86_64
./mklocalrepo.sh
cd /root/xcat2/core-snap
./mklocalrepo.sh
```

2.2.3 Install xCAT 2.0 software & Its Dependencies

```
yum clean metadata
yum install xCAT.x86_64
```

2.2.4 Test xCAT installation

```
source /etc/profile.d/xcat.sh
tabdump site
```

2.2.5 Update xCAT 2.0 software

If you need to update the xCAT 2.0 rpms later, download the new version of <http://xcat.sf.net/yum/core-rpms-snap.tar.bz2> (if the management node does not have access to the internet) and then run:

```
yum update '*xCAT*'
```

If you have a service node stateless image, don't forget to update the image with the new xCAT rpms (see Build the service node stateless image):

```
cp -pf /etc/yum.repos.d/*.repo
/install/netboot/fedora8/x86_64/service/rootimg/etc/yum.repos.d
yum --installroot=/install/netboot/fedora8/x86_64/service/rootimg update '*xCAT*'
packimage -o fedora8 -p service -a x86_64
```

2.2.6 Setup Yum for Fedora8 Node Installs

```
umount /root/xcat2/fedora8
cd /root/xcat2
copycds Fedora-8-x86_64-DVD.iso
copycds Fedora-8-ppc-DVD.iso
```

The copycds commands will copy the contents of the DVDs to /install/fedora8/<arch>.

Edit /etc/yum.repos.d/fedora.repo and change:

```
baseurl=file:///root/xcat2/fedora8
to
baseurl=file:///install/fedora8/x86_64
```

3.0 xCAT Hierarchy using Service nodes

In large clusters it is desirable to have more than one node (the Management Node) handle the installation of the compute nodes. We call these additional nodes service nodes. You can have one or more service nodes setup to install groups of compute nodes.

The service nodes need to communicate with the xCAT2.0 database on the Management Node and run xCAT command to install the nodes. The service node will be installed with the xCAT code and required the PostgreSQL Database be setup instead of SQLite Default database. PostgreSQL allows a client to be setup on the service node such that the service node can access (read/write) the database on the Management Node (Master Node) from the service node.

If you do not plan on using service nodes, you can skip this section 3 and continue to use the SQLite Default database setup during the installation.

3.1 Switching to PostgreSQL Database

To setup the postgresql database on the Management Node follow these steps.

This example assumes:

- 192.168.0.1: ip of master
- xcatdb: database name
- xcatadmin: database role (aka user)
- cluster: database password
- 192.168.0.10 & 192.168.0.11: service nodes

Substitute your address and desired userid , password and database name as appropriate.

The following rpms should be installed from the Fedora8 media on the Management Node (and service node when installed). These are required for postgresql.

```
1. yum install perl-DBD-Pg postgresql-server postgresql
```

2. Initialize the database :

```
service postgresql initdb
```

```
3. service postgresql start
```

```
4. su - postgres
```

```
5. createuser -P xcatadmin
```

```
Enter password for new role: cluster
```

```
Enter it again: cluster
```

```
Shall the new role be a superuser? (y/n) n
```

```
Shall the new role be allowed to create databases? (y/n) n
```

```
Shall the new role be allowed to create more new roles? (y/n) n
```

```
6. createdb -O xcatadmin xcatdb
```

```
7. exit
```

```
8. cd /var/lib/pgsql/data/
```

```
9. vi pg_hba.conf
```

Lines should look like this (with your IP addresses substituted). This allows the service nodes to access the DB.

```
local all all ident sameuser
# IPv4 local connections:
host all all 127.0.0.1/32 md5
host all all 192.168.0.1/32 md5
host all all 192.168.0.10/32 md5
host all all 192.168.0.11/32 md5
```

where 192.168.0.10 and 11 are service nodes.

```
10.vi postgresql.conf
```

```
set listen_addresses to '*':
```

```
listen_addresses = '*' This allows remote access.
```

Note: Be sure to uncomment the line

```
11.service postgresql restart
```

```
12.chkconfig postgresql on
```

13. Backup your data to migrate to the new database

```
mkdir -p ~/xcat-dbback
```

```
dumpxCATdb -p ~/xcat-dbback
```


14. /etc/sysconfig/xcat should contain these lines, substitute your cluster facing address for 192.168.0.1, and user and password are xcatadmin cluster in this instance – skip this??

```
XCATCFG='Pg:dbname=xcatdb;host=192.168.0.1|xcatadmin|cluster'  
export XCATCFG  
XCATROOT=/opt/xcat  
export XCATROOT
```

15. copy /etc/sysconfig/xcat to /install/postscripts/sysconfig/xcat for installation on the service nodes.
– skip this??
chmod 700 /etc/sysconfig/xcat

16. /etc/xcat/cfgloc should contain the following line, again substituting your info. This points the xCAT database access code to the new database.

```
Pg:dbname=xcatdb;host=192.168.0.1|xcatadmin|cluster
```

17. copy /etc/xcat/cfgloc to /install/postscripts/etc/xcat/cfgloc for installation on the service nodes.
mkdir -p /install/postscripts/etc/xcat
cp /etc/xcat/cfgloc /install/postscripts/etc/xcat/cfgloc
18. chmod 700 /etc/xcat/cfgloc

19. source /etc/sysconfig/xcat #read the text into the current shell – skip this??

20. You can add . /etc/sysconfig/xcat to a setup shell script in /etc/profile.d, so the XCATROOT and XCATCFG environment variables are setup when you login. – skip this??

21. Restore your database to postgresql:
XCATBYPASS=1 restorexCATdb -p ~/xcat-dbback

22. Start the xcatd daemon using the postgresql database
service xcatd restart

23. Run this command to get correct Master node name known by ssl:
openssl x509 -text -in /etc/xcat/cert/server-cert.pem -noout | grep Subject:
this will display something like:
Subject: CN=mgt.cluster

24. Update the policy table with mgt.cluster output from the command:
chtab priority=5 policy.name=<mgt.cluster> policy.rule=allow
Note: this name must be an MN name that is known by the service nodes.

25. Make sure the site table has the following settings (using tabdump, tabedit, chtab):

```
#key,value,comments,disable
"xcatiport","3002",,,
"xcatdport","3001",,,
"master","mn20",,,
```

where 11.16.0.1 and mn20 are the ip address and hostname of the management node as known by the service nodes.

26. Verify the policy table contains:

```
#priority,name,host,commands,noderange,parameters,time,rule,comments,disable
"1","root",,,,,,"allow",,
"2",,"getbmcconfig",,""allow",,
"3",,"nextdestiny",,""allow",,
"4",,"getdestiny",,""allow",,
"5","mn20",,,,,,"allow",,
```

3.2 Define the service nodes in the database

For this example, we have two service nodes rra000 and rrb000. To add the service nodes to the database run the following commands to add and update the service nodes' attributes in the site, nodelist and noderes tables. Note: service nodes are required to be defined with group “service”. The commands below are using the group “service” to update all service nodes.

Note: For table attribute definitions run `tabdump -d <table name>`

3.2.1 Define Service Nodes and bmc in nodelist table

```
nodeadd rra000,rrb000 groups=service,ipmi,all
```

3.2.2 Define Service Nodes in noderes table

```
chtab node=service noderes.netboot=pxe noderes.installnic=eth0
noderes.primarynic=eth0
```

3.2.3 Define Service Nodes in ipmi table

```
chtab node=service ipmi.bmc='|^(.+)$|($1)bmc|' ipmi.username=USERID
ipmi.password=PASSWORD
```

3.2.4 Define Service Nodes in nodehm table

```
chtab node=service nodehm.cons=ipmi nodehm.mgt=ipmi nodehm.serialspeed=19200
nodehm.serialflow=hard nodehm.serialport=0
```

3.2.5 Define Service Nodes in nodetype table

```
chtab node=service nodetype.arch=x86_64 nodetype.os=fedora8 nodetype.nodetype=osi
```

3.2.6 Set Necessary Attributes in site Table

```
chtab key=defserialport site.value=0
chtab key=defserialspeed site.value=19200
chtab key=xcatserver site.value=rra000,rrb000
```

Note: this last line should be removed when the code no longer uses this.

3.2.7 Define Service Node OS and Profile attributes

```
chtab node=service nodetype.os=fedora8 nodetype.profile=service
```

4.0 Setup Services

4.1 Setup networks Table

All networks in the cluster must be defined in the networks table. When xCAT was installed, makenetworks ran which created an entry in this table for each of the networks the management node is on. We will update the entry for the network for the management node and create one for each CU.

```
chtab net=11.16.0.0 networks.netname=mvnet networks.mask=255.255.0.0
  networks.mgtifname=eth4 networks.gateway=9.114.88.190
  networks.dhcpserver=11.16.0.1 networks.tftpserver=11.16.0.1
  networks.nameservers=11.16.0.1 networks.dynamicrange=11.16.1.210-11.16.1.250
chtab net=11.17.0.0 networks.netname=cuanet networks.mask=255.255.0.0
  networks.mgtifname=eth1 networks.gateway=11.17.255.254
  networks.dhcpserver=11.17.0.1 networks.tftpserver=11.17.0.1
  networks.nameservers=11.17.0.1 networks.dynamicrange=11.17.1.200-11.17.1.250
chtab net=11.18.0.0 networks.netname=cubnet networks.mask=255.255.0.0
  networks.mgtifname=eth1 networks.gateway=11.18.255.254
  networks.dhcpserver=11.18.0.1 networks.tftpserver=11.18.0.1
  networks.nameservers=11.18.0.1 networks.dynamicrange=11.18.1.200-11.18.1.250
```

Disable the entry for the public network (connected to the outside world):

```
chtab net=9.114.88.160 networks.netname=public networks.disable=1
```

4.2 Setup DNS

Set nameserver, forwarders and domain in the site table:

```
chtab key=nameservers site.value=11.16.0.1 # IP of mgmt node
chtab key=forwarders site.value=9.114.8.1,9.114.8.2 # site DNS servers
chtab key=domain site.value=cluster.net # domain part of the node hostnames
```

Edit /etc/hosts to be similar to:

```
127.0.0.1      localhost.localdomain localhost
::1           localhost6.localdomain6 localhost6
192.168.2.100 b7-eth0
192.168.100.1  b7
192.168.100.10 blade1
```

```
192.168.100.11 blade2
192.168.100.12 blade3
172.30.101.133 amm3
```

Run:

```
makedns
```

Setup /etc/resolv.conf:

```
search cluster.net
nameserver 11.16.0.1
```

Start DNS:

```
service named start
chkconfig --level 345 named on
```

4.3 Define AMMs as nodes

```
nodeadd bca01-bca04 groups=mm,all
nodeadd bcb01-bcb04 groups=mm,all
#nodeadd swa01-swa04 groups=mm,all # do not think we need to define these??
#nodeadd swb01-swb04 groups=mm,all # do not think we need to define these??
chtab node=mm nodehm.mgt=blade
chtab node=mm mp.mpa='|(.*)|($1)|'
```

4.4 Setup AMM

Note: currently the network settings on the MM (both for the MM itself and for the switch module) need to be set up with your own customized script. Eventually, this will be done by xCAT through lsslp, finding it on the switch, looking in the switch table, and then setting it in the MM.

```
rspconfig mm snmpcfg=enable sshcfg=enable
rspconfig mm pd1=redwoperf pd2=redwoperf
rpower mm reset
```

Note: should also set ntp settings using rspconfig, once MN is configured as NTP server.

Test the ssh set up with:

```
psh -l USERID@mm info -T mm[1]
```

TIP to update firmware:

Put CNETCMUS.pkt in /tftpboot

```
telnet AMM
env -T mm[1]
update -v -i TFTP_SERVER_IP -l CNETCMUS.pkt
```

TIP for SOL to work best telnet to nortel switch (default pw is “admin”) and type:

```
/cfg/port intl/gig/auto off  
Do this for each port (I.e. int2, int3, etc.)
```

4.5 Startup TFTP

```
mknb x86_64  
service tftpd restart
```

5.0 Define Compute Nodes in the Database

5.1 Setup the nodelist Table

The nodelist table contains a node definition for each node in the cluster. We have provided a script to automate these definitions for the RR cluster.

`/opt/xcat/share/xcat/tools/mkrrnodes` will allow you to automatically define as many nodes as you would like to and setup nodegroups needed to manage those nodes. See `man mkrrnodes`.

For example, running `mkrrnodes` will define the following nodes with the assigned groups in the nodelist table. These nodegroups will be used in additional xCAT Table setup so that an entry does not have to be made for every node.

```
/opt/xcat/share/xcat/tools/mkrrnodes -C a -R 001,012  
/opt/xcat/share/xcat/tools/mkrrnodes -C b -R 001,012
```

adds to the nodelist table entries like the following:

```
"rra001a", "rra001,ls21,cua,opteron,compute,tb,all,rack01",,,  
"rra001b", "rra001,qs22,cua,cell,cell-b,compute,all,tb,rack01",,,  
"rra001c", "rra001,qs22,cua,cell,cell-c,compute,all,tb,rack01",,,  
"rra002a", "rra002,ls21,cua,opteron,compute,tb,all,rack01",,,  
"rra002b", "rra002,qs22,cua,cell,cell-b,compute,all,tb,rack01",,,  
"rra002c", "rra002,qs22,cua,cell,cell-c,compute,all,tb,rack01",,,
```

5.2 Set Up the nodehm table

```
chtab node=opteron-cua nodehm.cons=blade nodehm.mgt=blade nodehm.conserver=rra000  
nodehm.serialspeed=19200 nodehm.serialflow=hard nodehm.serialport=1  
chtab node=cell-cua nodehm.cons=blade nodehm.mgt=blade nodehm.conserver=rra000  
nodehm.serialspeed=19200 nodehm.serialflow=hard nodehm.serialport=0  
chtab node=opteron-cub nodehm.cons=blade nodehm.mgt=blade nodehm.conserver=rrb000  
nodehm.serialspeed=19200 nodehm.serialflow=hard nodehm.serialport=1
```

```
chtab node=cell-cub nodehm.cons=blade nodehm.mgt=blade nodehm.conserver=rrb000
nodehm.serialspeed=19200 nodehm.serialflow=hard nodehm.serialport=0
```

When Table.pm supports where strings on rows that contain regex's (or I think when the servicenode table is used to determine if conserver should be set up??), the above lines can be replaced with:

```
chtab node=tb nodehm.cons=blade nodehm.mgt=blade nodehm.conserver='|rr(.).*|
rr($1)000|' nodehm.serialspeed=19200 nodehm.serialflow=hard
```

5.3 Set Up the mp Table

```
chtab node=opteron mp.mpa="|rr(.) (\d+)\D|bc(\$1) (sprintf('%02d', ((\$2-1)/3+1)))|"
mp.id='|rr. (\d+)\D| (((\$1-1)%3)*4+1) | '
chtab node=cell-b mp.mpa="|rr(.) (\d+)\D|bc(\$1) (sprintf('%02d', ((\$2-1)/3+1)))|"
mp.id='|rr. (\d+)\D| (((\$1-1)%3)*4+3) | '
chtab node=cell-c mp.mpa="|rr(.) (\d+)\D|bc(\$1) (sprintf('%02d', ((\$2-1)/3+1)))|"
mp.id='|rr. (\d+)\D| (((\$1-1)%3)*4+4) | '
```

5.4 Setup Conserver

```
makeconservercf
service conserver stop
service conserver start
```

Test a few nodes with rpower and rcons.

5.5 Setup the noderes Table

The noderes table will define for the node or nodegroup, the service node used to service the node or group, the type of network booting supported, the node which is the tftpserver, dhcpserver, etc as known by the node.

If you are using Service Nodes:

For each node or nodegroup defined in the noderes table change the service node attribute in the noderes table to point to the name or ip address of it's service node.

```
chtab node=opteron noderes.netboot=pxe noderes.servicenode='|rr(.).*|rr($1)000|'
noderes.xcatmaster='|rr(.).*|rr($1)000-eth1|' noderes.installnic=eth0
noderes.primarynic=eth0
chtab node=cell noderes.netboot=yaboot noderes.servicenode='|rr(.).*|rr($1)000|'
noderes.xcatmaster='|rr(.).*|rr($1)000-eth1|' noderes.installnic=eth0
noderes.primarynic=eth0
```

Will not need this when it properly defaults to xcatmaster

```
chtab node=opteron noderes.tftpserver='|rr(.).*|rr($1)000-eth1|'
chtab node=cell noderes.tftpserver='|rr(.).*|rr($1)000-eth1|'
```

If you are not using Service Nodes:

```
chtab node=opteron noderes.netboot=pxe noderes.xcatmaster=mn20 nodehm.serialport=1
  noderes.installnic=eth0 noderes.primarynic=eth0
chtab node=cell noderes.netboot=yaboot noderes.xcatmaster=mn20
  nodehm.serialport=0 noderes.installnic=eth0 noderes.primarynic=eth0
```

5.5.1 Sample noderes table

Your noderes table will end up looking like this (if you use service nodes):

```
#node, servicenode, netboot, tftpserver, nfsserver, monserver, kernel, initrd, kcmdline, nf
  sdir, serialport, installnic, primarynic, xcatmaster, current_osimage, next_osimage, co
  mments, disable
"opteron", "|rr(.).*|rr($1)000|", "pxe", "|rr(.).*|rr($1)000-
  eth1|",,,,,,,,,,"1", "eth0", "eth0", "|rr(.).*|rr($1)000-eth1|",,,,,
"cell", "|rr(.).*|rr($1)000|", "yaboot", "|rr(.).*|rr($1)000-
  eth1|",,,,,,,,,,"1", "eth0", "eth0", "|rr(.).*|rr($1)000-eth1|",,,,,
"service", "pxe",,,,,,,,,,"1", "eth0", "eth0",,,,,,
```

5.5.2 Setting up which services run on the Service Nodes

Note: if in the noderes table you have an assigned servicenode for a node, you must make sure you have that service started on that service node by having an entry for it in the servicenode table. If you leave a field blank in the servicenode table, the default is to start that service on that node. For RoadRunner we are starting all services on all service nodes. To do this, run:

```
chtab node=service servicenode.nameserver=1 servicenode.dhcpserver=1
  servicenode.tftpserver=1 servicenode.nfsserver=1 servicenode.conserver=1
  servicenode.monserver=1 servicenode.ldapservers=1 servicenode.ntpservers=1
  servicenode.comments='Starts all services on all service nodes'
```

5.6 Setup nodetype table

Define the OS and profile type for building the stateless image.

```
chtab node=opteron nodetype.os=fedora8 nodetype.arch=x86_64
  nodetype.profile=compute nodetype.nodetype=osi
chtab node=cell nodetype.os=fedora8 nodetype.arch=ppc64 nodetype.profile=compute
  nodetype.nodetype=osi
```

5.6.1.1 Sample nodetype table

Your nodetype table will look something like this:

```
#node, os, arch, profile, nodetype, comments, disable
"service", "fedora8", "x86_64", "service", "osi",,,
"opteron", "fedora8", "x86_64", "compute", "osi",,,
"cell", "fedora8", "ppc64", "compute", "osi",,,
```

5.7 Setup passwords in passwd table

Add needed passwords to the passwd table to support installs.

```
chtab key=system passwd.username=root passwd.password=cluster
chtab key=blade passwd.username=USERID passwd.password=PASSWORD
chtab key=ipmi passwd.username=USERID passwd.password=PASSWORD
```

5.8 Verify the tables

To verify that the tables are set correctly, run lsdef on a service node, opteron blade, and cell blade:

```
lsdef rra000,rra001a,rra001b
```

5.9 Setup deps Table for proper boot sequence

The following is an example of how you can setup the deps table to ensure the triblades boot up in the proper sequence. The 1st row tells xCAT the opteron blades should not be powered on until the corresponding cell blades are powered on. The 2nd row tells xCAT the cell blades should not be powered off until the corresponding opteron blades are powered off.

```
chtab node=opteron deps.nodedep='|rr(.\\d+)a|rr($1)b,rr($1)c|' deps.msdelay=5000
  deps.cmd=on
chtab node=cell deps.nodedep='|rr(.\\d+).|rr($1)a|' deps.msdelay=5000 deps.cmd=off
```

Verify the dependencies are correct:

```
nodels rra001a deps.nodedep
nodels rra001b deps.nodedep
```

5.10 Set Up Postscripts to be Run on the Nodes

Add names of postscripts that should be run for all nodes by using the xcatdefaults row of the postscripts table. (xCAT automatically fills in this table with defaults during a new install of the xCAT software on the management node, so you may not have to do this step.)

```
chtab node=xcatdefaults postscripts.postscripts=syslog,remoteshell
```

Also add postscripts that should be run on the service nodes:

```
chtab node=service
  postscripts.postscripts=configgeth,servicenode,xcatserver,xcatclient
```

5.11 Get MAC addresses

```
getmacs tb
```

Don't think we need this anymore:


```
rinv tb macs | perl -pi -e 's/([^\:]*):.*?ress (\d): (00(:[0-9A-F]{2}){5})/nodech \
  1 mac.mac=\3 #\2/' | grep \#1 > /tmp/setmacs.sh
source /tmp/setmacs.sh
```

To verify mac addresses in table:

```
tabdump mac
```

5.12 Setup DHCP

The dynamic ranges for the networks were set up already in chapter 4.

Define dhcp interfaces in site table. We use this weird value because our MN uses eth4 to communicate with the service nodes, and the service nodes use eth1 to communicate with the compute nodes.

```
chtab key=dhcpinterfaces site.value='mn20|eth4;service|eth1'
```

Ensure dhcpd is running:

```
service dhcpd start
```

Configure DHCP:

```
makedhcp -n
service dhcpd restart
```

6.0 Build the service node stateless image

The service node stateless images must contain not only the OS, but also the xCAT software. In addition, a number of files are added to the image to support the postgresql database access from the service node to the Management node, and ssh access to the nodes that the service nodes services. Note: the following example assumes you are building the stateless image on the Management Node.

1. Check the service node packaging to see if it has all the rpms required:

```
cd /opt/xcat/share/xcat/netboot/fedora/
vi service.pkglist service.exlist
```

Make sure service.pkglist has the following packages:

```
vi
dhcp
atftp
bind
nfs-utils
```

Edit service.exlist and include things you may need by removing the corresponding line. Make sure you remove:

```
./usr/lib/perl5*
```

While you are here, edit compute.pkglist and compute.exlist, adding and removing as necessary.

2. Run image generation:

```
cd /opt/xcat/share/xcat/netboot/fedora/  
./genimage -i eth0 -n tg3,bnx2 -o fedora8 -p service
```

3. Install xCAT code into the service node image:

```
rm -f /install/netboot/fedora8/x86_64/service/rootimg/etc/yum.repos.d/*  
cp -pf /etc/yum.repos.d/*.repo /install/netboot/fedora8/x86_64/service/rootimg/  
etc/yum.repos.d  
yum --installroot=/install/netboot/fedora8/x86_64/service/rootimg install  
xCATsn
```

4. Prevent DHCP from starting up until xcatd has had a chance to configure it:

```
chroot /install/netboot/fedora8/x86_64/service/rootimg  
chkconfig dhcpd off  
chkconfig dhcrelay off  
exit
```

5. Pack the image

```
packimage -o fedora8 -p service -a x86_64
```

6. To update the xCAT software in the image at a later time:

```
yum --installroot=/install/netboot/fedora8/x86_64/service/rootimg update '*xCAT*'  
packimage -o fedora8 -p service -a x86_64
```

6.1 Configure the Service Node BMCs??

It seems like we missed a step of having the rack mounted nodes automatically discovered when powered on, by having xcat respond to the dhcp request, check the switch for the port #, assign the hostname, and configure the BMC on the node. This also requires that the switch table be set up.

6.2 Install the Service Nodes

```
nodeset service netboot  
rpower service boot  
wcons service # make sure DISPLAY is set to your X server/VNC or  
rcons <one-node-at-a-time> # or do rcons for each node  
tail -f /var/log/messages
```

6.3 Test Service Node installation

- ssh to the service nodes.

- Check to see that the xcat daemon xcatd is running.
- Run some database command on the service node, e.g tabdump site, or nodels, and see that the database can be accessed from the service node.
- Check that /install and /tftpboot are mounted on the service node from the Management Node.

Right now, have to start conserver, until Ling fixes that bug:

```
service conserver start
```

7.0 iSCSI Install QS22 Blade

Note: in these instructions, substitute your management node IP address for 11.16.0.1.

```
yum install yaboot-xcat scsi-target-utils
chtab key=iscsidir site.value=/install/iscsi
```

Pick a QS22 blade for the iSCSI install that can access the management node. Add it as a node (and its management module, if necessary):

```
nodeadd mvqs21b groups=compute,iscsi
nodeadd bca2 groups=mm2
```

Make sure the root userid and password are in the iscsi table

```
chtab node=mvqs21b iscsi.userid=root iscsi.passwd=cluster iscsi.server=11.16.0.1
```

Other table settings:

```
chtab node=mvqs21b noderes.nfssserver=11.16.0.1 nodehm.serialport=0
  noderes.netboot=yaboot noderes.installnic=eth0 noderes.primarynic=eth0
chtab node=mvqs21b nodetype.os=fedora8 nodetype.arch=ppc64 nodetype.profile=iscsi
  nodetype.nodetype=osi iscsi.server=11.16.0.1
chtab node=mvqs21b nodehm.mgt=blade nodehm.cons=blade nodehm.serialspeed=19200
  nodehm.serialflow=hard
chtab node=bca2 nodehm.mgt=blade
chtab node=mvqs21b mp.mpa=bca2 id=2
chtab node=bca2 mp.mpa=bca2
```

```
getmacs mvqs21b
```

Put mvqs21b and bca2 in /etc/hosts, then:

```
makedns
makedhcp -n
```

```
service tgt restart
nodech mvqs21b iscsi.file=
setupiscsidev -s8192 mvqs21b
```

```
nodeset mvqs21b install
rpower mvqs21b boot
```

NOTE: for reinstall:

```
chtab node=mvqs21b nodetype.profile=iscsi # don't need this?
nodeset mvqs21b install
rpower mvqs21b boot
```

7.1 Build QS22 Stateless image

1. Logon to the qs22 blade:

```
ssh mvqs21b
mkdir /install
mount 11.16.0.1:/install /install
```

2. Create fedora.repo:

```
cd /etc/yum.repos.d
rm -f *.repo
```

Put the following lines in /etc/yum.repos.d/fedora.repo:

```
[fedora]
name=Fedora $releasever - $basearch
baseurl=file:///install/fedora8/ppc64
enabled=1
gpgcheck=0
```

3. Test with: yum search gcc

4. Copy the executables and files needed from the Management Node:

```
cd /root
scp 11.16.0.1:/opt/xcat/share/xcat/netboot/fedora/genimage .
scp 11.16.0.1:/opt/xcat/share/xcat/netboot/fedora/geninitrd .
scp 11.16.0.1:/opt/xcat/share/xcat/netboot/fedora/compute.ppc64.pkglist .
```

5. Generate the image:

```
./genimage -i eth0 -n tg3 -o fedora8 -p compute
```

NOTE: iSCSI, QS22, tg3, all slow, take a nap

7.2 Boot the QS22 Stateless image

On the Management Node:

1. Adding Service Node ssh keys – **Don't think we need to do this**, because the private & public keys on the service node will be the same as the management node

If you wish to be able to ssh from your service nodes to their compute nodes, you will have to follow these steps to add the additional required keys to the install image on the service node before the image is installed.

```
ssh rra000
ssh-keygen -t rsa
#take defaults and answer no to passcode/passphrase message when generating
keys
cat /root/.ssh/id_rsa.pub >>
    /install/netboot/fedora8/ppc64/compute/rootimg/root/.ssh/authorized_keys
```

Repeat the above steps for rrb000

2. Edit fstab in the image:

```
cd /install/netboot/fedora8/ppc64/compute/rootimg/etc
cp fstab fstab.ORIG
```

Edit fstab. **Change:**

```
devpts /dev/pts devpts gid=5,mode=620 0 0
tmpfs /dev/shm tmpfs defaults 0 0
proc /proc proc defaults 0 0
sysfs /sys sysfs defaults 0 0
```

to:

```
proc /proc proc rw 0 0
sysfs /sys sysfs rw 0 0
devpts /dev/pts devpts rw,gid=5,mode=620 0 0
#tmpfs /dev/shm tmpfs rw 0 0
compute_ppc64 / tmpfs rw 0 1
none /tmp tmpfs defaults,size=10m 0 2
none /var/tmp tmpfs defaults,size=10m 0 2
```

3. Pack the image:

```
packimage -o fedora8 -p compute -a ppc64
```

4. Install the image on all the QS22 blades:

```
nodeset cell netboot
rpower cell boot
```

7.3 To Update QS22 Stateless image

1. Before YUM/RPM commands (or genimage):

```
rm /install/netboot/fedora8/ppc64/compute/rootimg/var/lib/rpm/__.db.00*
```

2. To update the image by running genimage, add packages to compute.ppc64.pkglist and rerun genimage
3. To update image using YUM:

```
rm -f /install/netboot/fedora8/ppc64/compute/rootimg/etc/yum.repos.d/*
cp /etc/yum.repos.d/*.repo
   /install/netboot/fedora8/ppc64/compute/rootimg/etc/yum.repos.d
```

Now install vi into the image:

```
yum --installroot=/install/netboot/fedora8/ppc64/compute/rootimg install vi
```

4. To update image using RPM:

```
rpm --root /install/netboot/fedora8/ppc64/compute/rootimg -Uvh
   /install/fedora8/ppc64/Packages/vim-minimal-7.1.135-1.fc8.ppc.rpm
```
5.

```
packimage -o fedora8 -p compute -a ppc64
```

7.4 Build and Install QS22 Compressed Image

On the QS22 blade:

```
yum install kernel-devel gcc squashfs-tools
```

On internet connected node:

```
svn co http://xcat.svn.sf.net/svnroot/xcat/xcat-dep/trunk/aufs
```

7.4.1 Build aufs

```
cd aufs
tar jxvf aufs-2-6-2008.tar.bz2
cd aufs
mv include/linux/aufs_type.h fs/aufs/
cd fs/aufs/
patch -p1 < ../../../aufs-standalone.patch
chmod +x build.sh
./build.sh

# ls -lh aufs.ko
-rw-r--r-- 1 root root 3.5M 2008-03-10 14:20 aufs.ko

strip -g aufs.ko
cp aufs.ko /root
```

7.4.2 Generate the compressed image

```
cd /opt/xcat/share/xcat/netboot/fedora
```

```
./geninitrd -i eth0 -n tg3,squashfs,aufs,loop -o fedora8 -p compute -l $(expr 100 \* 1024 \* 1024)
```

7.4.3 Pack and install the compressed image

On the Management Node:

```
yum install squashfs-tools
packimage -a ppc64 -o fedora8 -p compute -m squashfs
chtab node=cell nodetype.profile=compute nodetype.os=fedora8
nodeset cell netboot
rpower cell boot
```

7.4.4 Check Memory Usage

```
# ssh left "echo 3 > /proc/sys/vm/drop_caches;free -m;df -h"
              total          used          free          shared          buffers          cached
Mem:           3961            99          3861              0              0              61
-/+ buffers/cache:           38          3922
Swap:           0              0              0
Filesystem      Size  Used Avail Use% Mounted on
compute_ppc64  100M  220K  100M   1% /
none            10M    0    10M   0% /tmp
none            10M    0    10M   0% /var/tmp
```

Max for / is 100M, but only 220K being used (down from 225M), but wheres the OS?

Look at cached. 61M compress OS image. 3.5x smaller

As files change in hidden OS they get copied to tmpfs (compute_ppc64) with a copy on write. To reclaim space reboot. The /tmp and /var/tmp is for MPI and other Torque and user related stuff. if 10M is too small you can fix it. To reclaim this space put in epilogue:

```
umount /tmp /var/tmp; mount -a
```

Reboot cell as stateless, from management node to reclaim space:

```
nodeset cell netboot
xdsh cell reboot #be nice, iSCSI is still stateful, be kind to the state??
```

7.4.5 To Switch a Compute Blade to iSCSI for More Setup

To reboot rra047b as iscsi for more stateless setup fun:

```
nodech rra047b nodetype.profile=iscsi
nodeset rra047b iscsiboot
rpower rra047b boot
```

8.0 Build LS21 Stateless image

The LS21 image can be built on the Management Node since it is of the same architecture.

On the Management Node:

1. Check the compute node packaging to see if it has all the rpms required.

```
cd /opt/xcat/share/xcat/netboot/fedora/  
vi compute.exlist and compute.pkglist
```

For example to add vi to be installed on the node, add the name of the vi rpm to compute.pkglist

```
echo vi >>compute.pkglist
```

Include things you may need which are excluded, by editing compute.exlist.

For example, if you require `./usr/lib/perl5`, remove the following line:

```
./usr/lib/perl5*
```

2. Run image generation:

```
./genimage -i eth0 -n tg3,bnx2 -o fedora8 -p compute
```

3. Adding Service Node ssh keys – **Don't need to do this**, because the private & public keys on the service node will be the same as the management node

If you wish to be able to ssh from your service nodes to their compute nodes, you will have to follow these steps to add the additional required keys to the install image on the service node before the image is installed. (The keys were already generated on the service nodes in chapter 7.)

```
ssh rra000  
cat id_rsa.pub >>  
  /install/netboot/fedora8/x86_64/compute/rootimg/root/.ssh/authorized_keys
```

Repeat the above steps for rrb000

4. Edit fstab in the image

```
cd /install/netboot/fedora8/x86_64/compute/rootimg/etc  
cp fstab fstab.ORIG
```

Edit fstab:

Change:

```
devpts /dev/pts devpts gid=5,mode=620 0 0  
tmpfs /dev/shm tmpfs defaults 0 0  
proc /proc proc defaults 0 0  
sysfs /sys sysfs defaults 0 0
```


to:

proc	/proc	proc	rw 0 0
sysfs	/sys	sysfs	rw 0 0
devpts	/dev/pts	devpts	rw,gid=5,mode=620 0 0
#tmpfs	/dev/shm	tmpfs	rw 0 0
compute_x86_64	/	tmpfs	rw 0 1
none	/tmp	tmpfs	defaults,size=10m 0 2
none	/var/tmp	tmpfs	defaults,size=10m 0 2

5. Package the image

```
packimage -o fedora8 -p compute -a x86_64
```

6. Install the image on all the LS21 blades

```
nodeset opteron netboot  
rpower opteron boot
```

8.1 To Update the LS21 Stateless Image Later On

1. Before running YUM/RPM commands:

```
rm /install/netboot/fedora8/x86_64/compute/rootimg/var/lib/rpm/__.db.00*
```

2. To update image using YUM:

```
rm -f /install/netboot/fedora8/x86_64/compute/rootimg/etc/yum.repos.d/*  
cp /etc/yum.repos.d/*  
/install/netboot/fedora8/x86_64/compute/rootimg/etc/yum.repos.d
```

Now install, for example, vi into the image:

```
yum --installroot=/install/netboot/fedora8/x86_64/compute/rootimg install vi
```

3. To update image using RPM:

```
rpm --root /install/netboot/fedora8/x86_64/compute/rootimg -Uvh blah.rpm
```

4. Repackage:

```
packimage -o fedora8 -p compute -a x86_64
```

5. Install on all LS21 blades:

```
nodeset opteron netboot  
rpower opteron boot
```

8.2 Build and Install LS21 Compressed Image

On Management Node:

```
yum install kernel-devel gcc squashfs-tools
```

8.2.1 Build aufs

```
svn co http://xcat.svn.sf.net/svnroot/xcat/xcat-dep/trunk/aufs
```

```
cd aufs
tar jxvf aufs-2-6-2008.tar.bz2
cd aufs
mv include/linux/aufs_type.h fs/aufs/
cd fs/aufs/
patch -pl < ../../../aufs-standalone.patch
chmod +x build.sh
./build.sh
```

```
ls -lh aufs.ko
-rw-r--r-- 1 root root 3.2M 2008-02-27 13:09 aufs.ko
```

```
strip -g aufs.ko
cp aufs.ko /opt/xcat/share/xcat/netboot/fedora/
```

8.2.2 Generate and pack the compressed image

```
cd /opt/xcat/share/xcat/netboot/fedora
./geninitrd -i eth0 -n tg3,bnx2,squashfs,aufs,loop -o fedora8 -p service -l $(expr
  100 \* 1024 \* 1024)
```

```
packimage -a x86_64 -o fedora8 -p compute -m squashfs
```

NOTE: The -l and -t is the size of the / and /tmp,/var/tmp file systems in RAM

NOTE: To unsquash:

```
cd /install/netboot/fedora8/x86_64/service
rm -f rootimg.sfs
packimage -a x86_64 -o fedora8 -p service -m cpio
```

8.2.3 Install the image

```
nodeset opteron netboot
rpower opteron boot
```

8.2.4 Check Memory Usage

```
#ssh middle "echo 3 > /proc/sys/vm/drop_caches;free -m;df -h"
      total      used      free      shared      buffers      cached
Mem:    3969         82      3887         0         0         43
-/+ buffers/cache:    38      3930
Swap:    0         0         0
Filesystem      Size  Used Avail Use% Mounted on
compute_x86_64  100M  216K  100M   1% /
none            10M    0    10M   0% /tmp
none            10M    0    10M   0% /var/tmp
```

3x smaller.

9.0 Building QS22 Image for 64K pages

On Management Node:

```
cd /opt/xcat/share/xcat/netboot/fedora
cp compute.exlist compute.exlist.4k
echo "./lib/modules/2.6.23.1-42.fc8/*" >>compute.exlist
```

```
wget
  http://download.fedora.redhat.com/pub/fedora/linux/releases/8/Fedora/source/SRPM
  S/kernel-2.6.23.1-42.fc8.src.rpm
nodech mvqs21b nodetype.profile=iscsi
nodeset mvqs21b iscsiboot
rpower mvqs21b boot
```

On the blade:

```
ssh mvqs21b
mkdir /install
mount mgmt:/install /install
yum install rpm-build redhat-rpm-config ncurses ncurses-devel kernel-devel gcc
  squashfs-tools
rpm -Uivh kernel-2.6.23.1-42.fc8.src.rpm
rpmbuild -bp --target ppc64 /usr/src/redhat/SPECS/kernel.spec
cd /usr/src/redhat/BUILD/kernel-2.6.23
cp -r linux-2.6.23.ppc64 /usr/src/
cd /usr/src/kernels/$(uname -r)-$(uname -m)
find . -print | cpio -dump /usr/src/linux-2.6.23.ppc64/
cd /usr/src/linux-2.6.23.ppc64
make mrproper
cp configs/kernel-2.6.23.1-ppc64.config .config
make menuconfig
```

```
Kernel options --->
[*] 64k page size
Platform support --->
[ ] Sony PS3
<exit><exit><save>
```

```
Edit Makefile suffix:
EXTRAVERSION = .1-42.fc8-64k
```

```
make -j4
make modules_install
strip vmlinux
mv vmlinux /boot/vmlinuz-2.6.23.1-42.fc8-64k
cd /lib/modules/2.6.23.1-42.fc8-64k/kernel
find . -name "*.ko" -type f -exec strip -g {} \;
#mkinitrd /boot/initrd-2.6.23.1-42.fc8-64k.img 2.6.23.1-42.fc8-64k
```

```
#rm -f /boot/vmlinuz-2.6.23.1-42.fc8 /boot/initrd-2.6.23.1-42.fc8.img
#rm -rf /lib/modules/2.6.23.1-42.fc8
```

9.1 Rebuild aufs

Rebuild aufs.so:

```
rm -rf aufs
tar jxvf aufs-2-6-2008.tar.bz2
cd aufs
mv include/linux/aufs_type.h fs/aufs/
cd fs/aufs/
patch -pl < ../../../aufs-standalone.patch
chmod +x build.sh
./build.sh 2.6.23.1-42.fc8-64k
strip -g aufs.ko
cp aufs.ko /root
```

NOTE: patch genimage (??)

On blade:

```
cd /root
./genimage -i eth0 -n tg3 -o fedora8 -p compute
cd /lib/modules
cp -r 2.6.23.1-42.fc8-64k
    /install/netboot/fedora8/ppc64/compute/rootimg/lib/modules/
cd /boot
cp vmlinuz-2.6.23.1-42.fc8-64k /install/netboot/fedora8/ppc64/compute/kernel
```

9.2 Test unsquashed:

On blade:

```
cd /root
./geninitrd -i eth0 -n tg3 -o fedora8 -p compute -k 2.6.23.1-42.fc8-64k
```

On Management Node:

```
rm -f /install/netboot/fedora8/ppc64/compute/rootimg.sfs
packimage -a ppc64 -o fedora8 -p compute -m cpio
nodech mvqs21b nodetype.profile=compute nodetype.os=fedora8
gnodeset mvqs21b netboot
rpower mvqs21b boot
```

9.2.1 Check memory

```
# ssh left "echo 3 > /proc/sys/vm/drop_caches;free -m;df -h"
              total          used          free          shared          buffers          cached
Mem:           4012            495           3517             0             0             429
```

```

-/+ buffers/cache:          66          3946
Swap:                      0            0
Filesystem                  Size  Used Avail Use% Mounted on
compute_ppc64              2.0G  432M  1.6G  22% /
none                       10M    0   10M   0% /tmp
none                       10M    0   10M   0% /var/tmp

```

9.3 Test squash

On mvqs21b:

```

cd /root
./geninitrd -i eth0 -n tg3,squashfs,aufs,loop -o fedora8 -p compute -k
2.6.23.1-42.fc8-64k -l $(expr 100 \* 1024 \* 1024)

```

On Management Node:

```

rm -f /install/netboot/fedora8/ppc64/compute/rootimg.sfs
packimage -a ppc64 -o fedora8 -p compute -m squashfs #bug, must remove sfs first
nodech left nodetype.profile=compute nodetype.os=fedora8
nodeset left netboot
rpower left boot

```

9.3.1 Check memory

```

# ssh left "echo 3 > /proc/sys/vm/drop_caches;free -m;df -h"

```

	total	used	free	shared	buffers	cached
Mem:	4012	127	3885	0	0	65
-/+ buffers/cache:		61	3951			

```

Swap:                      0            0
Filesystem                  Size  Used Avail Use% Mounted on
compute_ppc64              100M  1.7M  99M   2% /
none                       10M    0   10M   0% /tmp
none                       10M    0   10M   0% /var/tmp

```

./lib/modules/* in compute.exlist: (??)

9.4 To Switch Back to 4K Pages

On blade:

```

cd /boot
cp -f vmlinuz-2.6.23.1-42.fc8 /install/netboot/fedora8/ppc64/compute/kernel
cd /root
./geninitrd -i eth0 -n tg3 -o fedora8 -p compute

```

OR

```
./geninitrd -i eth0 -n tg3,squashfs,aufs,loop -o fedora8 -p compute -l $(expr 100 \* 1024 \* 1024)
```

From Management Node:

```
rm -f /install/netboot/fedora8/ppc64/compute/rootimg.sfs  
packimage -a ppc64 -o fedora8 -p compute -m cpio
```

OR

```
packimage -a ppc64 -o fedora8 -p compute -m squashfs  
nodech mvqs21b nodetype.profile=compute nodetype.os=fedora8  
nodeset mvqs21b netboot  
rpower mvqs21b boot
```

10.0 Using NFS Hybrid for the Diskless Images

1. Make sure you have latest xCAT installed (later than Thu Apr 24 17:34:48 UTC 2008)
2. Get stateless cpio or squashfs set up and test, e.g.:

```
cd /opt/xcat/share/xcat/netboot/fedora  
./genimage -i eth0 -n tg3,bnx2 -o fedora8 -p compute
```

cpio

```
./geninitrd -i eth0 -n tg3,bnx2,loop -o fedora8 -p compute  
packimage -a x86_64 -o fedora8 -p compute -m cpio
```

Overhead: (large image with development tools installed)

	total	used	free	shared	buffers	cached
Mem:	3969	740	3229	0	0	680
-/+ buffers/cache:		59	3910			
Swap:	0	0	0			
Filesystem	Size	Used	Avail	Use%	Mounted on	
compute_x86_64	2.0G	695M	1.3G	35%	/	
none	10M	0	10M	0%	/tmp	
none	10M	0	10M	0%	/var/tmp	
e326001:/home	32G	15G	16G	47%	/home	

squashfs (note order of modules important)

```
./geninitrd -i eth0 -n tg3,bnx2,squashfs,aufs,loop -o fedora8 -p compute  
packimage -a x86_64 -o fedora8 -p compute -m squashfs
```

Overhead: (large image with development tools installed)

```

                total        used        free        shared    buffers        cached
Mem:            3969          243        3726            0            0           206
-/+ buffers/cache:
Swap:           0            0            0
Filesystem      Size  Used Avail Use% Mounted on
compute_x86_64  2.0G  260K  2.0G   1% /
none            10M    0    10M   0% /tmp
none            10M    0    10M   0% /var/tmp
e326001:/home   32G   15G   16G  47% /home

```

```

nodeset noderange netboot
rpower noderange boot

```

3. Patch kernel and build new aufs.ko:

Get AUFS from CVS:

```

cd /tmp
mkdir aufs
cd /tmp/aufs
cvs -d:pserver:anonymous@aufs.cvs.sourceforge.net:/cvsroot/aufs login #CVS
password is empty
cvs -z3 -d:pserver:anonymous@aufs.cvs.sourceforge.net:/cvsroot/aufs co aufs
cd /tmp/aufs/aufs
cvs update

```

Install stuff

```

yum install rpm-build redhat-rpm-config ncurses ncurses-devel kernel-devel gcc
squashfs-tools

```

Kernel notes (x86_64 and ppc64):

```

cd /tmp
wget
http://download.fedora.redhat.com/pub/fedora/linux/releases/8/Fedora/source/
SRPMS/kernel-2.6.23.1-42.fc8.src.rpm
rpm -Uivh kernel-2.6.23.1-42.fc8.src.rpm
yum install redhat-rpm-config
rpmbuild -bp --target $(uname -m) /usr/src/redhat/SPECS/kernel.spec
cd /usr/src/redhat/BUILD/kernel-2.6.23
cp -r linux-2.6.23.$(uname -m) /usr/src/
cd /usr/src/kernels/$(uname -r)-$(uname -m)
find . -print | cpio -dump /usr/src/linux-2.6.23.$(uname -m)/
cd /usr/src/linux-2.6.23.$(uname -m)
make mrproper
cp configs/kernel-2.6.23.1-$(uname -m).config .config
patch -p0 < /tmp/aufs/aufs/patch/put_filp.patch
cd /tmp/aufs/aufs
cp -r include /usr/src/linux-2.6.23.$(uname -m)
cp -r fs/aufs /usr/src/linux-2.6.23.$(uname -m)/fs
cd /usr/src/linux-2.6.23.$(uname -m)

```

Edit fs/Kconfig and change (at end):

```

source "fs/nls/Kconfig"

```

```
source "fs/dlm/Kconfig"
```

To:

```
source "fs/nls/Kconfig"
source "fs/dlm/Kconfig"
source "fs/aufs/Kconfig"
```

Append to: fs/Makefile

```
obj-$(CONFIG_AUFS) += aufs/
```

```
make menuconfig
```

File system --->

```
<M> Another unionfs
---  These options are for 2.6.23.1-42.fc8
[ ]  Use simplified (fake) nameidata
      Maximum number of branches (127) --->
[*]  Use <sysfs>/fs/aufs
[ ]  Use inotify to detect actions on a branch
[ ]  NFS-exportable aufs
[ ]  Aufs as an readonly branch of another aufs
[ ]  Delegate the internal branch access the kernel thread
[ ]  show whiteouts
[*]  Make squashfs branch RR (real readonly) by default
[ ]  splice.patch for sendfile(2) and splice(2)
[*]  put_filp.patch for NFS branch
[ ]  lhash.patch for NFS branch
[ ]  fsync_super-2.6.xx.patch was applied or not
[ ]  deny_write_access.patch was applied or not
[ ]  Special handling for FUSE-based filesystem
[*]  Debug aufs
[ ]  Compatibility with Unionfs (obsolete)
```

Exit, Exit, Save

```
make -j4
make modules_install
make install
```

Whew!

4. Remove old aufs.ko:

```
cd /opt/xcat/share/xcat/netboot/fedora
rm -f aufs.ko
```

5. Boot NFS:

Create ifcfg-eth0:

```
cd /install/netboot/fedora8/x86_64/compute/rootimg/etc/sysconfig/networks-
scripts
```


Put in ifcfg-eth0:

```
ONBOOT=yes  
BOOTPROTO=none  
DEVICE=eth0
```

(This solves an intermittent problem where DHCP hoses IP long enough to hose NFS and then nothing works. It's also one less DHCP and it boots faster.)

Update modules:

```
cd /lib/modules  
cp -r * /install/netboot/fedora8/x86_64/compute/rootimg/lib/modules
```

Dump services:

```
cd /install/netboot/fedora8/x86_64/compute/rootimg/  
chroot .  
chkconfig --del messagebus  
chkconfig --del mdmonitor  
chkconfig --del netconsole  
exit
```

Edit fstab:

```
cd /install/netboot/fedora8/x86_64/compute/rootimg/etc
```

add this line:

```
sunrpc          /var/lib/nfs/rpc_pipefs rpc_pipefs rw 0 0
```

```
yum --installroot=/install/netboot/fedora8/x86_64/compute/rootimg install nfs-  
utils
```

```
cd /opt/xcat/share/xcat/netboot/fedora
```

```
./geninitrd -i eth0 -n tg3,bnx2,aufs,loop,sunrpc,lockd,nfs_acl,nfs -o fedora8 -  
p compute
```

```
packimage -a x86_64 -o fedora8 -p compute -m nfs
```

Notice helpful message:

NOTE: Contents of /install/netboot/fedora8/x86_64/compute/rootimg
MUST be available on all service and management nodes and NFS exported.

```
nodeset noderange netboot  
rpower noderange boot
```

Overhead: (large image with development tools installed)

	total	used	free	shared	buffers	cached
Mem:	3969	47	3922	0	0	8
-/+ buffers/cache:		38	3931			
Swap:	0	0	0			
Filesystem	Size	Used	Avail	Use%	Mounted on	
compute_x86_64	2.0G	300K	2.0G	1%	/	

none	10M	0	10M	0%	/tmp
none	10M	0	10M	0%	/var/tmp
e326001:/home	32G	15G	16G	47%	/home

11.0 Installing OpenLDAP

11.1 Setup LDAP Server

On the management node:

1. export /home (rw) for testing

```
echo '/home *(rw,no_root_squash,sync)' >> /etc/exports
exportfs -a
```
2. add a test userid "ibm"

```
useradd ibm
mkdir ~ibm/.ssh
mkdir ~ibm/.pbs_spool
```
3. Assign a password

```
passwd ibm
```
4. Generate root ssh keys for mn20 and give ibm id root ssh authority

```
ssh-keygen -t rsa -q -N "" -f ~ibm/.ssh/id_rsa
cp ~ibm/.ssh/id_rsa.pub ~ibm/.ssh/authorized_keys
```

```
vi ~ibm/.ssh/config
```

Add the following lines:

```
ForwardX11 yes
StrictHostKeyChecking no
FallbackToRsh no
BatchMode yes
ConnectionAttempts 5
UsePrivilegedPort no
Compression no
Cipher blowfish
UserKnownHostsFile /dev/null
CheckHostIP no
```

5. Set permissions :

```
chown -R ibm.ibm ~ibm
chmod 700 ~ibm/.ssh
chmod 600 ~ibm/.ssh/*
```

11.1.1 Install the LDAP rpms

```
yum install openldap-servers <-- could not get this package. I had to download
it from the fedora website .
http://download.fedora.redhat.com/pub/fedora/linux/releases/8/Everything/x86\_64/os/Packages/
( located in /tmp/lissa/tools/ldap)
```

The following rpms should be installed:

```
openldap-*
openldap-devel-*
openldap-clients-*
openldap-servers-*
```

11.1.2 Configure LDAP

```
cd /etc/openldap
```

6. edit slapd.conf

Comment out the following the two lines that start with suffix and rootdn:

```
database    bdb
#suffix     "dc=my-domain,dc=com"
#rootdn     "cn=Manager,dc=my-domain,dc=com"
```

Add the following information to the end of the file:

```
#xCAT start
#cluster.net:
suffix      "dc=cluster,dc=net"

#root access
rootdn      "cn=root,dc=cluster,dc=net"

#passwd generated with: slappasswd cluster - you should generate your own
password and use in the ldap commands below in place of cluster.

rootpw      {SSHA}ChnyPaCrc2uUZ006iRHy3zk4rEH7HNpL

# password hash algorithm
password-hash {SSHA}

# The userPassword by default can be changed by the entry owning it if they
# are authenticated. Others should not be able to see it, except the admin.
access to attrs=userPassword
    by dn="uid=admin,ou=People,dc=cluster,dc=net" write
    by anonymous auth
```

```

        by self write
        by * none
access to *
        by self write
        by * none

#
##password aging
access to attrs=shadowLastChange
        by dn="uid=admin,ou=People,dc=cluster,dc=net" write
        by self write
        by * read

```

7. Check the syntax of your slapd.conf file

```

slaptest -v -f /etc/openldap/slapd.conf
config file testing succeeded

```

8. cp /etc/openldap/DB_CONFIG.example /var/lib/ldap/DB_CONFIG

9. start ldap

```

service ldap start

```

11.1.3 Migrate Users

```

cd /usr/share/openldap/migration
cp migrate_common.ph migrate_common.ph.save

```

Edit migrate_common.ph and change the following lines to be:

```

$DEFAULT_MAIL_DOMAIN = "cluster.net";
$DEFAULT_BASE = "dc=cluster,dc=net";
$EXTENDED_SCHEMA = 1;

```

Run:

```

./migrate_base.pl >/tmp/base.ldif
./migrate_passwd.pl /etc/passwd >>/tmp/base.ldif
./migrate_group.pl /etc/group >>/tmp/base.ldif
cd /var/lib/ldap
service ldap stop
slapadd -l /tmp/base.ldif
chown ldap.ldap *
service ldap start

```

Test the database by searching for a the user ibm:

```

ldapsearch -x -v -D "cn=root,dc=cluster,dc=net" -w cluster -b
"ou=People,dc=cluster,dc=net" "uid=ibm"

```

Output should be as follows:

```

ldap_initialize( <DEFAULT> )
filter: uid=ibm

```

```

requesting: All userApplication attributes
# extended LDIF
#
# LDAPv3
# base <ou=People,dc=cluster,dc=net> with scope subtree
# filter: uid=ibm
# requesting: ALL
#
# ibm, People, cluster.net
dn: uid=ibm,ou=People,dc=cluster,dc=net
uid: ibm
cn: ibm
sn: ibm
mail: ibm@cluster.net
objectClass: person
objectClass: organizationalPerson
objectClass: inetOrgPerson
objectClass: posixAccount
objectClass: top
objectClass: shadowAccount
userPassword:: e2NyeXB0fSEh
shadowLastChange: 13998
shadowMax: 99999
shadowWarning: 7
loginShell: /bin/bash
uidNumber: 501
gidNumber: 501
homeDirectory: /home/ibm

# search result
search: 2
result: 0 Success

# numResponses: 2
# numEntries: 1

```

11.1.4 Add a User to LDAP

Setup a new user adduser.ldif file with the following contents:

```

dn: uid=ibm4,ou=People,dc=cluster,dc=net
uid: ibm4
cn: ibm4
sn: ibm4
mail: ibm4@cluster.net
objectClass: person
objectClass: organizationalPerson
objectClass: inetOrgPerson
objectClass: posixAccount
objectClass: top
objectClass: shadowAccount
shadowLastChange: 13998
shadowMax: 99999
shadowWarning: 7

```

```
loginShell: /bin/bash
uidNumber: 504
gidNumber: 504
homeDirectory: /home/ibm4
```

Run:

```
ldapadd -x -c -D "cn=root,dc=cluster,dc=net" -w cluster -f adduser1.ldif
adding new entry "uid=ibm4,ou=People,dc=cluster,dc=net"
```

Verify:

```
ldapsearch -x -v -D "cn=root,dc=cluster,dc=net" -w cluster -b
"ou=People,dc=cluster,dc=net" "uid=ibm4"
```

1.1.2 Set ibm4 userid password

Root sets the password to ibm4

```
ldappasswd -x -w cluster -D 'cn=root,dc=cluster,dc=net' -s ibm4
'uid=ibm4,ou=People,dc=cluster,dc=net'
Result: Success (0)
```

User sets the password to ibm44

```
ldappasswd -x -w ibm4 -D 'uid=ibm4,ou=People,dc=cluster,dc=net' -s ibm44
'uid=ibm4,ou=People,dc=cluster,dc=net'
Result: Success (0)
```

11.2 Setup LDAP Client

11.2.1 Install LDAP into the Image

```
yum --installroot=/install/netboot/fedora8/x86_64/compute/rootimg \
install openldap-clients nss_ldap nfs-utils vi
```

11.2.2 Update the LDAP Configuration in the Image

```
cd /install/netboot/fedora8/x86_64/compute/rootimg
```

Edit /etc/ldap.conf with these changes:

```
uri ldap://11.16.0.1/
host 11.16.0.1
base dc=cluster,dc=net
binddn cn=root,dc=cluster,dc=net
bindpw cluster
nss_base_passwd ou=People,dc=cluster,dc=net
nss_base_shadow ou=People,dc=cluster,dc=net
nss_base_group ou=Group,dc=cluster,dc=net
```

```
tls_cacertdir /etc/openldap/cacerts
pam_password md5
ssl no
```

Edit /etc/openldap/ldap.conf with these changes:

```
uri ldap://11.16.0.1
base dc=cluster,dc=net
```

Add ldap to the following three lines in /etc/nsswitch

```
passwd:      files ldap
shadow:      files ldap
group:       files ldap
```

Edit /etc/pam.d/system-auth, change (order important!):

change:

```
account      required      pam_unix.so
```

to:

```
account      sufficient    pam_ldap.so
account      required      pam_unix.so
```

Add to fstab to Mount /home for testing:

```
11.16.0.1:/home /home nfs timeo=14,intr 1 2
```

11.2.3 Build the Image and Install

Add the following rpms to the image for testing. Note: the order of modules in the geninitrd command is important!

```
cd /opt/xcat/share/xcat/netboot/fedora
./geninitrd -i eth0 -n tg3,bnx2,sunrpc,lockd,nfs,nfs_acl -o fedora8 -p compute
packimage -o fedora8 -p compute -a x86_64
nodeset rra001a netboot
rpower rra001a boot
```

11.2.4 Test LDAP Client

```
ssh to rra001a
```

Run:

```
ldapsearch -x -v -D "cn=root,dc=cluster,dc=net" -w cluster -b
"ou=People,dc=cluster,dc=net" "uid=ibm"
```

Check to see if you get output from the LDAP server as in Migrate Users.

Now authenticate the ibm users from LDAP by changing it's password and su to ibm.

```
passwd ibm
su - ibm
```

12.0 Setup Hierarchical LDAP

TBD

13.0 Install Torque

13.1 Setup Torque Server

```
cd /tmp
wget http://www.clusterresources.com/downloads/torque/torque-2.3.0.tar.gz
tar zxvf torque-2.3.0.tar.gz
cd torque-2.3.0
CFLAGS=-D__TRR ./configure \
    --prefix=/opt/torque \
    --exec-prefix=/opt/torque/x86_64 \
    --enable-docs \
    --disable-gui \
    --with-server-home=/var/spool/pbs \
    --enable-syslog \
    --with-scp \
    --disable-rpp \
    --disable-spool
make
make install
```

13.2 Configure Torque

```
cd /opt/torque/x86_64/lib
ln -s libtorque.so.2.0.0 libtorque.so.0
echo "/opt/torque/x86_64/lib" >>/etc/ld.so.conf.d/torque.conf
ldconfig
cp -f /opt/xcat/share/xcat/netboot/add-on/torque/xpbsnodes /opt/torque/x86_64/bin/
cp -f /opt/xcat/share/xcat/netboot/add-on/torque/pbsnodestat
/opt/torque/x86_64/bin/
```

Create /etc/profile.d/torque.sh:

```
export PBS_DEFAULT=mn20
export PATH=/opt/torque/x86_64/bin:$PATH
chmod 755 /etc/profile.d/torque.sh
source /etc/profile.d/torque.sh
```

13.3 Define Nodes

```
cd /var/spool/pbs/server_priv
```



```
nodels '/rr.*a' groups | sed 's/: groups:/' | sed 's/,/ /g' | sed 's/$/ np=4/'
>nodes
```

13.4 Setup and Start Service

```
cp -f /opt/xcat/share/xcat/netboot/add-on/torque/pbs /etc/init.d/
cp -f /opt/xcat/share/xcat/netboot/add-on/torque/pbs_mom /etc/init.d/
cp -f /opt/xcat/share/xcat/netboot/add-on/torque/pbs_sched /etc/init.d/
cp -f /opt/xcat/share/xcat/netboot/add-on/torque/pbs_server /etc/init.d/
chkconfig --del pbs
chkconfig --del pbs_mom
chkconfig --del pbs_sched
chkconfig --level 345 pbs_server on
service pbs_server start
```

13.5 Install pbstop

```
cp -f /opt/xcat/share/xcat/netboot/add-on/torque/pbstop /opt/torque/x86_64/bin/
chmod 755 /opt/torque/x86_64/bin/pbstop
```

13.6 Install Perl Curses for pbstop

```
yum install perl-Curses
```

13.7 Create a Torque Default Queue

```
echo "create queue dqe
set queue dqe queue_type = Execution
set queue dqe enabled = True
set queue dqe started = True
set server scheduling = True
set server default_queue = dqe
set server log_events = 127
set server mail_from = adm
set server query_other_jobs = True
set server resources_default.walltime = 00:01:00
set server scheduler_iteration = 60
set server node_pack = False
set server keep_completed=300" | qmgr
```

13.8 Setup Torque Client (x86_64 only)

13.8.1 Install Torque

```
cd /opt/xcat/share/xcat/netboot/add-on/torque
./add_torque /install/netboot/fedora8/x86_64/compute/rootimg mn20 /opt/torque
x86_64 local
```

13.8.2 Configure Torque

13.8.2.1 Set Up Access

```
cd /install/netboot/fedora8/x86_64/compute/rootimg/etc/security
echo "-:ALL EXCEPT root:ALL" >>access.conf
cp access.conf access.conf.BOOT
cd /install/netboot/fedora8/x86_64/compute/rootimg/etc/pam.d
```

Edit system-auth and replace:

```
account    sufficient    pam_ldap.so
account    required      pam_unix.so
```

with:

```
account    required      pam_access.so
account    sufficient    pam_ldap.so
account    required      pam_unix.so
```

13.8.2.2 Set Up Node to Node ssh for Root

This is needed for cleanup:

```
cp /root/.ssh/* /install/netboot/fedora8/x86_64/compute/rootimg/root/.ssh/
cd /install/netboot/fedora8/x86_64/compute/rootimg/root/.ssh/
rm known_hosts
```

Setup the config file:

```
echo "StrictHostKeyChecking no
FallBackToRsh no
BatchMode yes
ConnectionAttempts 5
UsePrivilegedPort no
Compression no
Cipher blowfish
CheckHostIP no" >config
```

13.8.3 Pack and Install image

```
packimage -o fedora8 -p compute -a x86_64
nodeset opteron netboot
rpower opteron boot
```

14.0 Setup Moab

14.1 Install Moab

```
cd /tmp
wget http://www.clusterresources.com/downloads/mwm/moab-5.2.1-linux-x86_64-
torque.tar.gz
tar zxvf /tmp/moab-5.2.1-linux-x86_64-torque.tar.gz
```

```
cd moab-5.2.1
./configure --prefix=/opt/moab
make install
```

14.2 Configure Moab

```
mkdir -p /var/spool/moab/log
mkdir -p /var/spool/moab/stats
```

Create /etc/profile.d/moab.sh:

```
export PATH=/opt/moab/bin:$PATH
```

```
chmod 755 /etc/profile.d/moab.sh
source /etc/profile.d/moab.sh
```

Edit moab.cfg and change:

```
RMCFG[mn20]          TYPE=NONE
```

to:

```
RMCFG[mn20]          TYPE=pbs
```

Append to moab.cfg :

```
NODEAVAILABILITYPOLICY    DEDICATED:SWAP
JOBNODEMATCHPOLICY        EXACTNODE
NODEACCESSPOLICY          SINGLEJOB
NODEMAXLOAD                .5
JOBMAXSTARTTIME           00:05:00
DEFERTIME                  0
JOBMAXOVERRUN             0
LOGDIR                     /var/spool/moab/log
LOGFILEMAXSIZE            10000000
LOGFILEROLLDEPTH          10
STATDIR                   /var/spool/moab/stats
```

14.2.1 Start Moab

```
cp -f /opt/xcat/share/xcat/netboot/add-on/torque/moab /etc/init.d/
chkconfig --level 345 moab on
service moab start
```

15.0 References

- XCAT2.0 Beta Cookbook - <http://xcat.svn.sourceforge.net/svnroot/xcat/xcat-core/trunk/xCAT-client-2.0/share/doc/xCAT2.0.pdf>